ES9465 MFP/ ES9475 MFP Specifications





Outstanding A3 colour multifuntion printers for large workgroups and busy departments

Productive, secure, efficient and easy to use. The ES9465 MFP and ES9475 MFP multifunction printers offer enterprise-class features to help businesses reduce printer total cost of ownership and carbon footprint.

The ES9465 MFP and ES9475 MFP multifuntion printers seamlessly integrate into your document workflow. This makes the range ideal for larger workgroups and departments with multiple users that need access to fast devices capable of fulfilling their day to day workflow requirements.

Ultimate flexibility

A range of paper feed and finishing options mean the unit can be tailored to suit various customer needs.

- Configurations available: Cabinet (1,200 sheets), Paper Feed Pedestal (1,750 sheets) or Large Capacity Feeder (3,200 sheets)
- Finishing options include 2-tray Inner finisher (ES9465 MFP only), Multi-Stapling finisher and Saddle-Stitch finisher
- 100-sheet Multi-Purpose Tray (MPT)
- Paper sizes from A6 to SRA3
- Paper weight from 60 to 280gsm
- A4 print/copy speeds up to 50ppm
- Time to first copy, from 6.1 secs colour and 4.7 secs mono (ES9475 MFP)
- High capacity 38.4k mono and 33.6k colour toner cartridge

Enhanced efficiency through ease of use

The ES9465 MFP and ES9475 MFP come with an extremely user-friendly and intuitive large colour touch screen display that gives exceptionally easy access to a large range of functions, such as printing, scanning, faxing and copying.

- 9' (23cm) adjustable, ergonomic, colour touch screen
- Customisable Menu function for individual user setup

Print smart by printing in-house

Digital LED print technology combined with versatile paper handling allows users to produce high quality professional documents on a multitude of different media, without having to rely on a professional print house or a high street print shop.

- Advanced image processing
- Wide range of paper weights, sizes and types
- ICC colour profiles
- Extensive output options from posters to booklets and N-up

Flexible open architecture for simple integration into your document workflow

The embedded platform, sXP (smart Extendable Platform), enhances productivity by allowing users to electronically capture, distribute and manage document workflows.

 Customisable open architecture for ease of integration

- Scan preview to make sure correct images are processed and distributed
- Store any document in your personal inbox for easy retrieval with E-Filing
- 100-sheet RADF automatic duplex (double sided) document scanning

Advanced security to protect your business

Advanced security features to preserve the confidentiality of sensitive data. Enhanced user authentication prevents unauthorised access.

- Secure Hard Disk Drive
- Secure networking with SNMPv3, SSL-Encryption
- Role Based Access Control
- Secure Print/PDF
- Hard Disk Drive secure data overwrite enabler option available

Improving efficiency and your carbon foot print

A wide range of eco features help reduce energy consumption, environmental impact and ongoing costs.

- Digital LED reduces power consumption
- Sleep Mode reduces standby power
- Duplex printing, copying, scanning and faxing reduces paper usage

EXECUT VE SER ES

Energy Star and Blue Angel compliant

ES9465 MFP and ES9475 MFP - Colour and Mono Multifunction Products

Printer		PAPER HANDLING	
Print speed	ES9465 MFP: A4: 35ppm colour/mono; A3: 18ppm colour/mono ES9475 MFP: A4: 50ppm colour/mono; A3: 25ppm colour/mono	Standard paper capacity (80gsm)	Cabinet: Tray 1: 550 sheets; Tray 2: 550 sheets; Multi-purpose tray: 100 sheets; RADF: 100 sheets
Time to first print	ES9465 MFP: Approx 8.1 seconds colour, 6.4 seconds mono ES9475 MFP: Approx 6.1 seconds colour 4.7 seconds mono		Paper Feed Pedestal (PFP): Tray 1: 550 sheets; Tray 2: 550 sheets; Tray 3: 550 sheets; Optional Tray 4: 550 sheets (Draw Module); Multi-purpose tray: 100 sheets; RADF: 100 sheets
Warm up time	Power On: 27 seconds; Low-power mode and Sleep Mode: 12 seconds		Large Capacity Feeder (LCF): Tray 1: 550 sheets; Tray 2: 550 sheets; Tray 3: 2,000 sheets (A4 only); Multi-purpose tray: 100
Processor	Power PC Appliedmicro APM86190 1.2GHz		sheets; RADF: 100 sheets
Resolution	600 x 600dpi, 5 bit; 600 x 1200 dpi, 1 bit (PS only)	Maximum paper capacity	3,200 sheets of 80gsm
Scanner	80 PCL fonts & 136 PostScript fonts, PCL Bitmap fonts	Paper sizes	Tray 1: A3, A4, A5, B4, B5; Tray 2/PFP/Drawer Module: SRA3, A3 A4, A5, B4, B5; LCF: A4; Multi-purpose tray: SRA3, A3, A4, A5 B B5, OHP. Support Custom size: Width 100-305mm Length 148- 1200mm; RADF: A3, A4, A5; Duplex: SRA3, A3, A4, A5, B4, B5
Resolution	Max. 600 x 600dpi		Tray 1/2/PFP/Drawer Module: 60 to 256gsm; LCF: 64 to 105gsn
Speed	Up to 73spm (300 x 300dpi)	Paper weight	Multi-purpose tray: 52 to 280gsm; RADF(Simplex): 35 to
Colour depth	Output 24 bit (8 bit x 3 RGB)		157gsm; RADF(Duplex): 50 to 157gsm; Duplex: 60 to 256gsm
Document input	Up to 100 sheet RADF and Platen	Duplex and RADF	Standard
Contrast	9 Levels	Paper output	A4: 550 sheets of 80gsm; A3: 300 sheets of 80gsm
Format	JPEG, TIFF-Multi/Single page, PDF-Multi/Single Page, Slim PDF, XPS-Multi/Single Page	Options: paper output	Inner Finisher: 2 trays, 600-sheet capacity (ES9465 MFP only); Multi-Stapling Finisher: 2 trays, 2,250-sheet capacity; Saddle-Stitch Finisher: 2 trays, 3,250-sheet capacity
Address book	LDAP & internal address book		, , <u>, , , , , , , , , , , , , , , , , </u>
Scan to	WS Scan, Scan to USB, Scan to E-Mail, Scan to File (SMB, FTP, FTPS, IPX/SPX, local), Scan to e-Filing, Meta Scan (option)	GENERAL FEATURES	
(Memory	Standard: 2GB RAM + 320GB HDD
Сору			Operating temperature/humidity: 10°C to 30°C / 20% to 85% F
First copy out	ES9465 MFP: Approx 8.1 seconds colour, 6.4 seconds mono ES9475 MFP: Approx 6.1 seconds colour 4.7 seconds mono	Environment	Storage temperature/humidity: -10°C to 35°C / less than 85% RH (w/ supplies)
Speed colour and mono	ES9465 MFP: A4: 35cpm; A3: 18cpm ES9475 MFP: A4: 50cpm; A3: 25cpm	Power supply	Single phase 220–240VAC, frequency 50/60Hz
Resolution	600 x 600dpi	Power consumption	Max: 2000W; Sleep: <1W
	25-400% (platen), 25-200% (RADF) in 1% increments	Noise level	Operating: <71dB(A); Standby: <51dB(A);
Maximum copies	* ** * *		Power save: Background level (with full options)
Fax (Optional)		Dimensions (HxWxD)	Cabinet: 1191 x 585 (max 820) x 644 (max 790) mm PFP: 1191 x 585 (max 665) x 644 (max 725) mm LCF: 1191 x 585 (max 665) x 644 (max 730) mm
Connectivity	RJ11 x 2 (Line/Tel) PSTN	Weight ⁴	Cabinet: 101.3kg; PFP: 102.8kg; LCF: 112.5kg
Speed	33.6kbps2.4Kbps (automatic fallback)	Warranty	1 year standard parts warranty
Groups	Max. 200 groups, 400 destinations/group	Product order numbers	ES9465 MFP with Cabinet: 45744606
Broadcast	Max. 400 destinations		ES9465 MFP with PFP: 45744604 ES9465 MFP with LCF: 45744605
Page memory	Max. 100 Jobs, 400 destinations/job, 2000 destinations, Max. 1000 pages/file		ES9475 MFP with Cabinet: 45744609 ES9475 MFP with PFP: 45744607 ES9475 MFP with LCF: 45744608
INTERFACE AND SOFTWARE		Accessories (Opper Number	
Connectivity	10/100/1000baseT, 2 x Host USB 2.0, 1 x Device USB 2.0	Accessories (Order Number	
Printer languages	PCL5e, PCL5c, PCL6, PS3, PDF, XPS 10Base-T/100Base-TX Ethernet Card with internal Web Server	Paper Feeders / Furniture	Cabinet: 45588601; PFP: 45587501; LCF: 45587601; Drawer Module: 45588001 (PFP only)
Network & protocols	for MFP and network card set-up and management. Includes POP3/APOP and SMTP Mail client for submission of print jobs and for alerts. All major network protocols supported - TCP/IP ARP, IPv4/v6, ICMPv4/v6, TCP, UDP, LPR, FTP, TELNET, HTTP(IPP), DHCP, SNMPv1/v3, DNS, Dynamic DNS, Secure DDNS, Bonjour, WINS, SSL/TLS, SMTP, POP3, SNTP, WSDPrint, JetDirect protocols, NetBIOSoverTCP, Kerberos. NetWare 6.5 with full NDS and NDPS support:- PServer, RPrinter, NDPS supported via Novell NDPS Gateway. Ethertalk:- ELAP, AARP, DDP, AEP, NBP, ZIP, RTMP, ATP, PAP. NetBEUI:- SMB, NetBIOS. Other:- EAP.	Finisher Units	Multi-Stapling: 45587301; Saddle-Stitch: 45587101; Inner: 45587001 (ES9465 MFP only)
		Hole Punch Units	2, 4 and Swedish: 45011202/3/4 (Inner Finisher); 2, 4 and Swedish: 45587402/3/4 (Multi-Stapling or Saddle- Stitch Finisher)
		Fax	Fax board: 45588702; 2nd line fax unit: 44955102
		Connectivity	Wireless LAN Module: 45517901; Anntena: 45518001
		Card Reader	HID: 45518501; Mifare: 45518601
OS Compatibility ¹	Windows 7 SP1 (32-bit & 64-bit) / Vista SP2 (32-bit & 64-bit) / XP SP3 (32-bit) / XP 64-bit / Server 2008 (32-bit & 64-bit) / Server 2003 SP1 (32-bit & 64-bit)/ Server 2008 R2 SP1 (64-bit); Mac OS X 10.4.11, 10.5.7, 10.6.7, 10.7.2, 10.8; Linux Redhat 7.x, 8.x, 9.x / Redhat Enterprise WS2 / SuSE Linux v7.x, 8.x, 9.x / Mandrake v7.x, 8.x, 9.x / Turbo Linux 8, 10; Solaris v2.6, 2.7, 7.8, 8, 9, 10 / HP-UK v10.20, 11.x / AIX 4.3.3	Enablers	Data Overwrite: 45518101; IPSec: 45518401; Meta scan: 45518201
			Manual Pocket: 44985501; Damp Heater: 45588401; Work Tray: 44954701; Bridge Kit: 45588101; Job Separator: 45011902
		CONSUMABLES (ORDER NUMBE	RS)
Advanced networking & security	IPv6 Phase2, IEEE2600.1, IEEE 802.1x, IPSec ² , SNMPv3, SSL3/ TLS HTTPS encryption, Secure Erase ³ , Data Encryption ³ , MAC address filtering, IP address filtering, Secure Print	Toner cartridges* (33,600 pages)	Cyan: 45643511; Magenta: 45643510; Yellow: 45643509
		Toner cartridges* (38,400 pages)	Black: 45643512
Operator Panel		Waste Toner Box	
LCD Touch-screen	9' (23cm) Colour backlit LCD touch screen & key top; 28 Hard	(120,000 pages Mono) (30,000pages Colour)	45639502

¹Check local OKI Executive Series website for latest driver releases and OS compatibility; ²Optional IPsec Enabler required. ³Optional Disk Overwrite Kit required; ⁴Including all consumables

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.

OKI SYSTEMS (UK) LTD

Blays House, Wick Road Egham, TW20 0HJ United Kingdom T +44 (0)1784 274 300 F +44 (0)1784 274 301 WWW.OKIEXECUTIVESERIES.CO.UK



