





NEW PIAGGIO RANGE, CITY SOUND

The city moves to the beat of Piaggio: unmistakeable style, attention to detail, leading technological engines in terms of low emissions, wide range of accessories for unique riding pleasure.

Piaggio confirms its ability to reinvent itself in harmony with its cosmopolitan personality and attentive to the evolving needs of its users; engine research goes hand in hand with new design solutions and cutting-edge eco-sustainable solutions.

A true flagship of the range, X10 is the evolution of the GT with a structure cut from an automobile patter which alternates concavity and convexity, culminating in the short, coupé-inspired tail. Conceived for par excellence admirers, X10 has plenty of added features such as full body paintwork enriched by chromium and satin finishing, the most advanced lighting system available in the two-wheeler segment, the brand new 350 engine, top level Piaggio technology and ergonomics implemented to the advantage of travelling comfort.

Dedicated to those looking for a versatile scooter, New Fly is the symbol of simple, fluid and quick urban mobility, available in two ecological engine versions. The compact dimensions and balanced volumes make it extremely easy to handle; it also has a low and comfortable saddle for an easy seating position and a spacious footboard which ensures significant riding comfort.

A summary of Piaggio innovations in environmental terms as well, MP3 Hybrid is the first and only hybrid, plug-in scooter in the world, equipped with a long life lithium ion battery which can be recharged directly on the domestic power grid. This vehicle is a must for anyone making a choice based on ecology: the exclusive Piaggio hybrid engine combines the power of a combustion engine with the environmentally friendliness of a quick electric motor.

X10 500 ie…350 ie…125 ie

A UNIQUE LINE

Modern, sleek and attractive lines, designed in a wind tunnel, a wealth of equipment and top notch performance. X10 is the latest addition to the prestigious Piaggio GT range: an authentic flagship on two wheels, dedicated to those who want maximum comfort in a bike that is 100% Italian elegance. With the new Piaggio X10 riding becomes a daily luxury.

- Exclusive finishing and full-body paintwork
- LED light assembly with D.R.L. (Daytime Running Light)
 Automotive style instrument panel
- and backlit controls on the handlebar
 Also available in the Executive version with ABS/ASR and multimedia support
- Complete range of engines: 125, 350 and, only in the Executive version, 500 cc
- Reduced seating difference between rider and passenger
- Rider-passenger footrest more than 1 metre long
- Large helmet compartment and spacious leg shield back plate compartments
- 280 mm dual front brake with standard combined braking
- Rear suspension electrically adjustable (on 500 version)
- USB and 12V socket

ACCESSORIES

- Large top box kit, colour-coded with vehicle (holds 2 flip up helmets)
- Medium top box kit, colour-coded with vehicle (holds 1 flip up helmet and 1 jet helmet)
- Sport top fairing
- Scooter cover
- Leg cover
- Electronic alarm system
- Multimedia support
- Gel comfort saddle
- Passenger backrest
- Tunnel bag
- Top box inner bag
- Piaggio Jet helmet in carbon fibre
- PMP (Piaggio Multimedia Platform)



GRIGIO BLU ORIONE MIDNIGHT

MARRONE BIANCO MERCURIO PERLA (Executive only)

100 102 103 0

box has not not not not not his his his not has not been been him

Executive Equipment - ABS / ASR -- Multimedia support -

of this pair has been not start that





MP3 BUSINESS LT 500 ie...300 ie

DEDICATED TO THOSE WHO WANT TO MOVE AROUND IN PROFESSIONAL AND ELEGANT STYLE

MP3 is the world's only scooter with the patented Piaggio guadrilateral front suspension layout. Its stability is incomparable in any riding conditions. MP3 combines maximum fun with a superior level of active safety. Now it has a new look and injection on every engine version. MP3 provides unique riding pleasure and comfort features of a true GT scooter. MP3 Business was conceived to meet the needs of those looking for safety with a professional and elegant style.

- Dual ignition MASTER 500 engine,
- 4-stroke, 4 valves, electronic injection
- 4-stroke, 4 valve QUASAR 300 engine with electronic injection
- Practical glove compartment pocket with three compartments under the windshield
- Windshield adjustable to 3 positions
- Double access to load compartment to store two flip up helmets
- 3 disc brakes with combined braking as standard equipment
- Electronic front suspension lock system park vehicle without using the stand

ACCESSORIES

- "Style" windshield
- "Comfort" windshield
- Large top box kit with tilting bracket (can hold two flip up helmets)
- Medium top box kit with tilting bracket (can hold one flip up helmet and one jet helmet)
- Leg cover
- Scooter cover
- Electronic alarm
- Specific mounting kit
- for TomTom Rider GPS
- Racing footrest kit
- Standard height gel comfort saddle
- Raised height gel comfort saddle
- Antitheft steering lock
- Copter helmet colour-coded with vehicle
- Piaggio Jet helmet in carbon fibre





GRIGIO MARRONE PLUTONE MERCURIO **BIANCO** PERLA

MP3 SPORT LT 500 ie···300 ie

MAXIMUM SAFETY AND PERFORMANCE WITH A SPORTY LOOK

MP3 Sport includes all the technical content of the Business version, standing out for its sport style details which emphasise its dvnamic character.

- Gloss black finishing
- Black rims
- Aluminium footrests
- Silver stitching on the saddle
- Sleek and aerodynamic rear view mirror
- Exclusive matt colour-schemes

ACCESSORIES

- "Style" windshield
- "Comfort" windshield
- · Large top box kit with tilting bracket (can hold two flip up helmets)
- Medium top box kit with tilting bracket (can hold one flip up helmet and one jet helmet)
- Standard height gel comfort saddle
- Raised height gel comfort saddle
- Leg cover
- Scooter cover
- Electronic alarm
- · Specific mounting kit
- for TomTom Rider GPS
- Antitheft steering lock
- Copter helmet colour-coded with vehicle
- Piaggio Jet helmet in carbon fibre

NERO

COSMO



MP3 Hybrid 300 ie

THE FIRST AND ONLY HYBRID SCOOTER ON THE MARKET. A TRUE RECORD BREAKER.

Its exclusive hybrid engine system, fine tuned by the Piaggio Group, combines the power of its combustion engine with respect for the environment and the quick response of an electric motor.

and has not seen that the local line and has had been up to a set of the local line line and

- The world's first and only scooter using hybrid technology, long-range lithium ion batteries and offering plug-in capability, charging directly from a domestic mains power socket
- Up to 60 km with one litre of fuel*
- Reduced emissions: only 40 g of CO₂ per km*
- Up 20 km range in full electric mode to circulate freely in areas restricted to internal combustion engines
- Ride by Wire electronic accelerator

ACCESSORIES

- "Style" windshield
- "Comfort" windshield
- Large top box kit
 with tilting bracket
- (capable of carrying two flip up helmets)
- Standard height gel comfort saddle
 Raised height gel comfort saddle
- Leg cover
- Scooter cover
- Electronic alarm
- Dedicated mounting kit for TomTom Rider navigator
- Racing footrest kit
- Dedicated helmet
- Antitheft steering lock

*use cycle 2/3 Hybrid Power, 1/3 electric



BIANCO PERLA



100 100

101 101

best has not use out out out the last has been and be to be

ten and ten our ten per con our and ten and ten and ten and ten and ten and

and some later

the set the set the

100 100 100





MP3 YOURBAN 300 ie MP3 YOURBAN LT 300 ie

THE MP3 IS NOW FOR EVERYONE!

MP3 Yourban is the compact three-wheeler with slender lines, agile and easy to handle, ideal for moving through traffic easily and in complete safety. Available with a 300 cc electronic injection engine, MP3 Yourban stands out for equipment and finishing at the top of its category.

- 300 4-stroke, 4 valve QUASAR engine with electronic injection
- Chassis designed to enhance its handling and agility features
- 13" front wheels
- 3 disc brakes for a safe and powerful braking (combined braking in the LT version)
- Quadrilateral front suspension layout with electronic roll blocking system
- Helmet compartment for two jet helmets with visors
- Mudguards colour-coded with the vehicle body
- Instrument panel complete with refined light blue illumination

ACCESSORIES

- Medium windshield
- High windshield
- Transparent hand guards
- Quick release rear top box kit colour-coded with vehicle
- Line of dedicated helmets compatible with Bluetooth system
- E-Power electronic alarm Leg cover, practical
- and quick to put on Scooter cover
- Antitheft steering lock
- Copter helmet colour-coded with vehicle
- Tunnel bag



ORIONE

COSMO



BIANCO IBIS PERLA

best from onto your your your your how how your your your your

 101 102 101

DI 123 124 II

100 102 100 100



MP3 YOURBAN SPORT 300 ie MP3 YOURBAN SPORT LT 300 ie

THE COMPACT SPORT SCOOTER

MP3 Yourban Sport combines the safety features, agility and handling of the MP3 family with a decisive and attractive look, enhanced by the exclusive colour-schemes in contrast with its black finishing.



- Black rims
- Red stitching on the saddle
- Dedicated sport colour-schemes

ACCESSORIES

- Medium windshield
- High windshield
- Transparent hand guards
- Quick release rear top box kit colour-coded with vehicle
- Line of dedicated helmets compatible with Bluetooth system
- E-Power electronic alarm
- Leg cover, practical
- and quick to put on
- Outdoor scooter cover
- Antitheft steering lock
- Copter helmet colour-coded with vehicle



the same same same size has been same and a

A 100 100 100 100



GRIGIO TITANIO LUNA OPACO

ten ten inn met inn der eine nie den mit mit mit ein mit inn mit bei den mit



- LEADER 125 engine*
- Double access to cargo compartment to store 2 flip up helmets or objects up to 80 cm long
- Maximum comfort: broad saddle. ergonomic handle and passenger backrest
- Analogue and digital instruments with onboard computer and rpm indicator
- Hazard control on handlebar

ACCESSORIES

- Extra large windshield with hand guards
- Top box kit with tilting luggage carrier
- Leg cover
- Scooter cover
- Electronic alarm
- Tunnel bag

NERO

METEORA

OPACO

the loss and the loss and the

100,000

100 ISN 100 ISN

100 107 100 to

* not available on the Italian market

EDITION SPORT



NERO

COSMO

BIANCO LUNA

GRIGIO ORIONE





BEVERLY SportTouring 350 ie

and had been

MORE EXCITEMENT

Beverly SportTouring is the highest performance and most technologically advanced tall-wheeled scooter on the market: the new engine combines the operating costs and lightness of a 300 cc with the performance of a 400 cc.

- 350 4-stroke, 4 valve engine
- with electronic fuel injection and more than 33 HP
- The maximum in performance
- and stability
- Absolute safety thanks
- to the 300 mm front disc
- Combined braking (standard version)
- Available in ABS/ASR version
- Spacious helmet compartment capable
- of holding two jet helmets
- 13 litre fuel tank
- for record setting range
- Refined and sporty style
- Smoked windshield as standard equipment

ACCESSORIES

- Transparent windshield
- Windshield
- Medium top box kit
- Large top box kit
- Leg cover
- Outdoor vehicle cover
- Scooter cover for garage
- Electronic alarm system
- Mechanical antitheft steering lock
- Tunnel bag
- Copter helmet colour-coded with vehicle





LUNA

NERO

LUCIDO



ARGENTO COMETA OPACO



BEVERLY 300 ie. 125 ie

THE EVOLUTION OF A LEADER

The functional elegance of the Beverly range, together with the technical popularity and the wealth of features, meets the needs of the rider in any conditions of use.

- 4-stroke, 4 valve QUASAR 300 engine with electronic injection
- 125 4-stroke, 4 valve engine with electronic injection
- Spacious helmet compartment capable of holding two jet helmets
- The only scooter in its segment featuring a 300 mm front disc brake
- Plenty of carefully designed accents
- · Great stability and easy handling in traffic

ACCESSORI

- Clear or tinted windshield
- Windshield
- Medium top box kit
- Large top box kit
- Leg cover
- Outdoor vehicle cover
- Scooter cover for garage
- Electronic alarm system
- Mechanical antitheft steering lock
- Tunnel bag
- Copter helmet colour-coded with vehicle

PERLA



....

the lost and lost

100 100 10



MERCURIO

GRIGIO ORIONE



101 100

100,000

And they say the

term too too too too too to



LIBERTY 150..125..50 4T..50 2T THE CITY HAS NEVER BEEN SO EASY

NEW **LIBERTY** Full Optional 125 EASE IS STANDARD FROM THE FACTORY

100 00

- LEADER 125 and 150 engines
- 50 2-stroke and 50 4-stroke engine
- High fuel economy
- Great agility and easy handling in traffic
- 16" wide front wheel for greater riding safety and stability
- Roomy flat footrest
- Helmet compartment capable of holding a demi-jet helmet

ACCESSORIES

- Windshield
- Top box kit, colour-coded with vehicle
- Embossed finish top box kit
- Scooter cover
- Universal leg cover
- Electronic alarm
- Antitheft steering lock
- Lowered saddle

NERO

COSMO



- Top box kit, colour-coded with vehicle as standard equipment
- Large enough for a flip-up helmet.
- Windshield as standard equipment. It is made in high quality, impact resistant and scratch proof metacrylate in 4 mm sheet

ACCESSORIES

- Scooter cover
- Universal leg cover
- Electronic alarm
- Antitheft steering lock
- Lowered saddle



NERO GALASSIA

BIANCO STELLA



box has not not not not not had had box not boy box box has her

(150/125 cc only)

GRIGIO PULSAR

BIANCO

PERLA

ARANCIO RAME LUCIDO (50 cc only)



PERSEO (150/125 cc only)

BRONZO

10,00



NEW FLY 125 ie 3V··50 4T 4V

SIMPLY FLY

The city is its natural habitat. Fly is an unbeatable vehicle for simplifying your daily movements. Style, comfort and safety on two wheels in the most classic Piaggio style. The new Piaggio Fly is mobility for all. Anywhere in the world.

- Italian and popular style
- 125 4-stroke, 3 valve engine with electronic injection
- 50 Hi-Per 4, 4-stroke, 4 valve engine for reduced fuel consumption and emissions
- The comfort of a mini GT
- Compact dimensions
- · Excellent comfort thanks to its low and ergonomic saddle
- Helmet compartment for 2 demi-jet helmets with visor
- Maximum functionality thanks to the flat footrest, double stand and refuelling access in the back shield 101 101 100 1

101 101

100 100 100

101 102 102

ACCESSORIES

- Top box kit with painted cover
- Embossed finish top box kit
- Windshield kit
- Anti-slip platform mat
- Perimeter trim
- Universal AWATECH leg cover
- Scooter cover
- Electronic alarm



101 102

101 101

202 203 202 203 203 203 20

100 100 100 100 100 100

101 102 102

101 101

the lot of the lot of the lot

101 102 101

10, 10, 10, 10

100 102 100 100

the loss and loss and the lo



10.01



NERO COSMO BIANCO



BLU

ROSSO IBIS

PERLA

100 100 100



FLY 100*..50 2T YOUR EVERYDAY FRIEND

- 100 4-stroke engine
- 50 Hi-Per 2, 2-stroke engine
- Maximum respect for the environment and high fuel economy
- Great comfort: ergonomic saddle, integrated passenger footrests and rear grab handle
- Large helmet compartment able to hold a flip up helmet
- 12" wheels make for great handling
- Low saddle and flat footrest for the utmost comfort and functionality

ACCESSORIES

- Windshield
- Top box kit
- Fumé windshield
- Electronic alarm
- Scooter cover

NERO

LUCIDO

- Universal leg cover
- Antitheft steering lock

*not available on the Italian market



NEW NRG Power DD / DT* MAXIMUM ENERGY

- New saddle
- New graphics
- Hi-Per 2, 2-stroke engine liquid cooled (DD version)
- Upside-down fork for excellent road holding
- Large helmet compartment able to hold a flip up helmet
- Oversize rear wheel
- for maximum riding stability • Analogue and digital instruments
- Braking system with front and rear disc (DD version)

ACCESSORIES

- Windshield
- Top box kit
- Universal leg cover
- Electronic alarm
- Antitheft steering lock

*not available on the Italian market







NERO

ARGENTO COMETA OPACO

BIANCO BLU CULT MIDNIGHT

101 101 101 102 101



EXCALIBUR



ALC: 102 102 103 103

BIANCO LUNA

10,000

101 123 123 1

test into one pass the set of the last the set into the set of the set

METEORA OPACO

OPACO

GRIGIO TITANIO

11



have not you have been not only not you and you was

ZIP 50 2T··50 4T THE CITY IS ITS NATURAL HABITAT



- New spirited graphics
- 50 Hi-Per 2, 2-stroke engine liquid cooled
- Sporty, quick and nimble
- Saddle adjustable to three positions

BIANCO

OTTICO

SPECIAL SERIES

SPECIAL

WHITE

SPECIAL

BLACK

• Large helmet compartment able to hold a flip up helmet

ACCESSORIES

- Windshield
- Top box kit
- Fumé windshield
- Universal leg cover
- Electronic alarm
- Antitheft steering lock



- 50 Hi-Per 2, 2-stroke engine liquid cooled
- Sporty, quick and nimble
- Saddle adjustable to three positions
 Large helmet compartment able ____ to hold a flip up helmet

ACCESSORIES

- Windshield
- Top box kit
- Fumé windshield
- Universal leg cover
- Electronic alarm
- Antitheft steering lock



10,000

LUCIDO

BIANCO LUNA



BLU NERO MIDNIGHT LUCIDO



100

TYPHOON 125..50 2T **RIDING PURE ENERGY**



- 50 Hi-Per 2, 2-stroke engine
- Fun to ride, safe, minimalist

 Convenient to use thanks to its compact dimensions and flat footrest

- Its strength is its simple design
- Large helmet compartment able to hold a flip up helmet
- Wide 12" tyres
- Large saddle for two people

ACCESSORIES

- Top box kit
- Windshield
- Leg cover
- Scooter cover
- Electronic alarm system
- Antitheft steering lock



OPACO

BIANCO CULT

10.00

-- -- -- --



NETTUNO OPACO



| TECHNICAL SPECIFICATIONS | Engii Bo |
|-----------------------------|-------------|
| - | F |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | ABS / A |

| | X10 | |
|----------------------------|--|--|
| | 500 ie | 350 ie (125 ie)* |
| Engine | 4-stroke 4-valve single cylinder engine | 4-stroke 4-valve single cylinder engine |
| Engine capacity | 493 cu cm | 330 сс (125 сс) |
| Bore x Stroke | 94 x 71 mm | 78 mm x 69 mm (57 mm x 48.6 mm) |
| Power | 30 kW -40.8 hp- at 7,250 rpm | 24.5 kW -33.3 hp- at 8,250 rpm (11 kW -15 hp- at 8,750 rpm) |
| Torque | 46 Nm at 5,250 rpm | 32.3 Nm at 6,250 rpm (12 Nm at 7,250 rpm) |
| Fuel system | Electronic injection | Electronic injection |
| Cooling | Liquid | Liquid |
| Lubrication | Wet sump | Dry sump (Wet sump) |
| Starter | Electric with oil-bath free wheel | Electric with oil-bath free wheel |
| Gearbox | CVT automatic variator | CVT automatic variator |
| Clutch | Automatic centrifugal dry clutch | Automatic multi disc wet centrifugal (Automatic, centrifugal dry) |
| Chassis | Double-cradle in high strength steel tube | Double-cradle in high strength steel tube |
| Front suspension | Hydraulic telescopic fork with Ø 41 mm stanchions | Hydraulic telescopic fork with Ø 35 mm stanchions |
| Rear suspension | Dual action single shock absorber with electronically adjustable spring preloading and progressive linkage | Double dual action hydraulic shock absorber with adjustable preloading to four positions |
| Brake front | Ø 280 mm disc with floating calliper and two pistons, combined braking | Ø 280 mm diam. dual disc with dual piston floating calliper, combined braking system |
| Brake rear | Ø 240 mm disc with dual piston floating calliper | Ø 240 mm disc with dual piston floating calliper |
| BS / ASR System | Standard | Standard on the Executive version |
| Tyre front | Tubeless 120/70 - 15" | Tubeless 120/70 - 15" |
| Tyre rear | Tubeless 150/70 - 13" | Tubeless 150/70 - 13" |
| Length/ /idth/Wheelbase | 2,265 mm / 800 mm / 1,640 mm | 2,265 mm / 800 mm / 1,625 mm |
| Saddle height | 760 mm | 760 mm |
| uel tank capacity | 15.5 l (2 l reserve) | 15.5 l (2 l reserve) |
| Emissions compliance | EURO 3 | EURO 3 |

| | MP3 HYBRID |
|----------------------------|--|
| | 300 ie |
| Internal combustion engine | 4-stroke 4-valve single cylinder engine |
| Engine capacity | / 278 сс |
| Bore x Stroke | 75 mm x 63 mm |
| Fuel system | 7 Electronic fuel injection with Ride by Wire throttle |
| Cooling | 7 Liquid |
| Lubrication | 7 Wet sump |
| Starte | r Electric |
| Electric moto | r Synchronous brushless permanent magnet motor |
| Power supply voltage | P Three-phase alternating current |
| Engine contro | / Digitally controlled inverter |
| Cooling system | 7 Forced air |
| Electric motor powe | r 2.6 kW -3.5 hp- |
| Electric motor torque | e 15 Nm |
| Hybrid powertrain powe | r 18.2 kW -24.8 hp- at 7,500 rpm |
| Hybrid powertrain torque | 28 Nm at 3,500 rpm |
| Gearbo, | CVT with torque server |
| Clutch | h Automatic, centrifugal dry clutch |
| Chassi | Double cradle in high strength tubular steel |
| Fron suspension | Articulated quadrilateral |
| Rea suspension | I Double dual action by draulie check abcorbor |
| Brake | Hydraulically operated (27/1) mm double disc |
| Brake rea | Hydraulically operated 0 240 mm disc |
| Length, Width/Wheelbase | 1 / 1/11 mm / /bl/mm / 1 /lyl/mm |
| Saddle heigh | t 780 mm |
| Fuel tank capacity | / 12 litres |
| Consumption | 60 km /l (combined cycle 2/3 hybrid; 1/3 electric) |
| Max range in electric mode | 20 km |
| Emission | 40 g/km (combined cycle 2/3 hybrid; 1/3 electric) |
| Emission. compliance | I FUBU 3 |

| | _ | |
|------------|---|---|
| | _ | |
| | _ | |
| le control | | |
| | | |
| | | |
| | | |
| r | | |
| | | |
| | | |
| | • | |
| | • | |
| | | |
| | | |
| | | 1 |
| | | ŝ |
| | | 1 |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | - | |
| | - | |
| | - | |
| 1 | - | |
| | - | |
| | | |

| | MP3 BUSINESS / SPORT | | MP3 YOURBAN / SPORT |
|----------------------------|--|--|---|
| | LT 500 ie | LT 300 ie | 300 ie / LT 300 ie |
| Engine | 4-stroke 4-valve single cylinder engine | 4-stroke 4-valve single cylinder engine | 4-stroke 4-valve single cylinder engine |
| Engine capacity | 493 cu cm | 278 сс | 278 сс |
| Bore x Stroke | 94 x 71 mm | 75 mm x 63 mm | 75 mm x 63 mm |
| Power | 29.5 kW -40.1 hp- at 7,250 rpm | 16.5 kW -22.5 hp- at 7,500 rpm | 16.6 kW -22.6 HP- at 7,500 rpm / LT 16.7 -22.7 HP at 7,750 rpm |
| Torque | 46.5 Nm at 5,250 rpm | 23.2 Nm at 6,500 rpm | 24 Nm at 6,000 rpm / LT 24 Nm at 5,750 rpm |
| Fuel system | Electronic injection | Electronic injection | Electronic injection |
| Cooling | Liquid | Liquid | Liquid |
| Lubrication | Wet sump | Wet sump | Wet sump |
| Starter | Electric | Electric | Electric |
| Gearbox | CVT with torque server | CVT with torque server | CVT with torque server |
| Clutch | Automatic centrifugal dry clutch | Automatic centrifugal dry clutch | Automatic centrifugal dry clutch |
| Chassis | Double cradle in high strength tubular steel | Double cradle in high strength tubular steel | Double cradle in high strength tubular steel |
| Front suspension | Articulated quadrilateral | Articulated quadrilateral | Articulated quadrilateral |
| Rear suspension | Double dual-action hydraulic shock absorber | Double dual-action hydraulic shock absorber | Double dual-action hydraulic shock absorber |
| Brake front | Hydraulically operated Ø 240 mm double disc | Hydraulically operated Ø 240 mm double disc | Hydraulically operated Ø 240 mm double disc |
| Brake rear | Hydraulically operated Ø 240 mm disc | Hydraulically operated Ø 240 mm disc | Hydraulically operated Ø 240 mm disc |
| Tyre front | Tubeless 120/70 - 12" | Tubeless 120/70 - 12" | Tubeless 110/70 - 13" |
| Tyre rear | Tubeless 140/70 - 14" | Tubeless 140/60 - 14" | Tubeless 140/60 - 14" |
| /Length Width/Wheelbase | 2,180 mm / 760 mm / 1,550 mm | 2,130 mm / 745 mm / 1,490 mm | 2,040 mm / 760 mm / 1,440 mm |
| Saddle height | 785 mm | 780 mm | 780 mm |
| Fuel tank capacity | 12 litres | 12 litres | 11 litres |
| Emissions compliance | Euro 2 | EURO 2 | EURO 3 / LT EURO 2 |

| | XEVO | BEVERLY | | |
|----------------------------|--|--|--|------|
| | 125** | SportTouring | 300 ie (125 ie)* | |
| Engine | 4-stroke 4-valve single cylinder engine | 4-stroke 4-valve single cylinder engine | 4-stroke 4-valve single cylinder engine | |
| Engine capacity | 124 cc | 330 cc | 278 сс (124 сс) | |
| Bore x Stroke | 57 mm x 48,6 mm | 78 mm x 69 mm | 75 mm x 63 mm (57 mm x 48.6 mm) | |
| Power | 11 kW -15 hp- at 10,000 rpm | 24.5 kW -33.3 hp- at 8,250 rpm | 16.3 kW -22.2 hp- at 7,250 rpm (11 kW -15 hp- at 9,250 rpm) | |
| Torque | 12 Nm at 8,000 rpm | 32.3 Nm at 6,250 rpm | 23 Nm at 5,750 rpm (12 Nm at 7,500 rpm) | |
| Fuel system | Carburettor | Electronic injection | Electronic injection | |
| Cooling | Liquid | Liquid | Liquid | |
| Lubrication | Wet sump | Dry sump | Wet sump | |
| Starter | Electric | Electric with oil-bath free wheel | Electric | |
| Gearbox | CVT with torque server | CVT automatic variator | CVT with torque server | |
| Clutch | Automatic centrifugal dry clutch | Automatic multi disc wet centrifugal | Automatic centrifugal dry clutch | |
| Chassis | Double cradle in high strength tubular steel | Double cradle in high strength tubular steel | Double cradle in high strength tubular steel | |
| Front suspension | Hydraulic telescopic fork | 35 mm hydraulic telescopic fork | Hydraulic telescopic fork | 10.1 |
| Rear suspension | Double hydraulic shock absorber with four- position spring preload adjustment | Double dual action hydraulic shock absorber with four-position spring preload adjustment | Double hydraulic shock absorber with four- position spring preload adjustment | |
| Brake front | Hydraulically operated Ø 260 mm disc | Hydraulically operated Ø 300 mm disc -combined braking or ABS/ASR version- | Hydraulically operated Ø 300 mm disc | |
| Brake rear | Hydraulically operated Ø 240 mm disc | Hydraulically operated Ø 240 mm disc -combined braking or ABS/ASR version- | Hydraulically operated Ø 240 mm disc | |
| Tyre front | Tubeless 120/70 - 14" | Tubeless 110/70 - 16" | Tubeless 110/70 - 16" | |
| Tyre rear | Tubeless 140/60 - 13" | Tubeless 150/70 - 14" | Tubeless 140/70 - 14" | |
| Length/ Width/Wheelbase | 2,070 mm / 760 mm / 1,490 mm | 2,215 mm / 760 mm / 1,560 mm | 2,150 mm / 780 mm / 1,535 mm | |
| Saddle height | 790 mm | 795 mm | 790 mm | |
| Fuel tank capacity | 12.5 litres | 13 litres | 13 litres | |
| Emissions compliance | EURO 3 | EURO 3 | EURO 3 | |

| | | LIBERTY | | NEW FLY | |
|---|----------------------------|---|---|---|--------|
| - | | 150 (125)* | 50 4T (50 2T)* | 125 3V | • |
| - | Engine | 4-stroke 2-valve single cylinder engine | Single cylinder Hi-Per 4, 4-stroke, 2 valve (Hi- Per 2, 2-stroke) | 4-stroke 3-valve single cylinder engine | |
| - | Engine capacity | 151 cc (124 cc) | 49.9 cc (49.4 cc) | 124 cc | - |
| - | Bore x Stroke | 62,8 mm x 48,6 mm (57 mm x 48,6 mm) | 39 mm x 41,8 mm (40 mm x 39,3 mm) | 52 mm x 58,6 mm | - |
| - | Power | 8.9 kW -12.1 hp- at 7,750 rpm (7.7 kW -10.5 hp- at 8,250 rpm) | 2.6 kW -3.5 hp- at 7,000 rpm (3.4 kW -4.6 hp- at 7,250 rpm) | 8.9 kW -12.1 hp- at 8,250 rpm | - |
| - | Torque | 11.8 Nm at 6,500 rpm (9.6 Nm at 7,250 rpm) | 3.7 Nm at 6,750 rpm (4.7 Nm at 6,750 rpm) | 10.7 Nm at 6,750 rpm | |
| - | Fuel system | Carburettor | Carburettor | Injection | |
| - | Cooling | Forced air | Forced air | Forced air | - |
| - | Lubrication | Wet sump | Wet sump (automatic mixer controlled accor- ding to throttle opening and engine speed) | Wet sump | - |
| 1 | Starter | Electric | Electric and kick starter | Electric | - |
| | Gearbox | CVT with torque server | CVT with torque server | CVT with torque server | - |
| đ | Clutch | Automatic centrifugal dry clutch | Automatic centrifugal dry clutch | Automatic centrifugal dry clutch | 100. 1 |
| | Chassis | High strength tubular steel single cradle frame | High strength tubular steel single cradle frame | Single cradle structure in tubular steel with pressed reinforcements | |
| | Front suspension | Hydraulic telescopic fork | Hydraulic telescopic fork | Hydraulic telescopic fork | |
| | Rear suspension | Hydraulic shock absorber with four-position spring preload adjustment | Hydraulic shock absorber | Hydraulic monoshock absorber | - |
| _ | Brake front | Hydraulically operated Ø 240 mm disc | Hydraulically operated Ø 240 mm disc | Hydraulically operated Ø 220 mm disc | - |
| - | Brake rear | Ø 140 mm drum | Ø 140 mm drum | Hydraulically operated Ø 220 mm disc | - |
| | Tyre front | Tubeless 90/80 - 16" | Tubeless 90/80 - 16" | Tubeless 120/70 - 12" | |
| - | Tyre rear | Tubeless 110/80 - 14" | Tubeless 110/80 - 14" | Tubeless 120/70 - 12" | - |
| _ | Length/ Width/Wheelbase | 1,935 mm / 760 mm / 1,325 mm | 1,935 mm / 760 mm / 1,320 mm | 1,850 mm / 720mm / 1,325 mm | |
| | Saddle height | 795 mm | 785 mm | 760 mm | |
| - | Fuel tank capacity | 7.5 litres | 6 litres | 7 Litres (including 1.5 litre reserve) | |
| - | Emissions compliance | EURO 3 | EURO 2 | EURO 3 | |

| | NEW FLY | FLY | | |
|----------------------------|---|---|---|---|
| | 50 4T | 100** | 50 2T | • |
| Engine | Hi-Per 4, 4-stroke 4 valve single cylinder | 4-stroke 2-valve single cylinder | Hi-Per 2, 2-stroke single cylinder | - |
| Engine capacity | 49.9 cc | 96.2 cc | 49.4 cc | - |
| Bore x Stroke | 39 mm x 41,8 mm | 50 mm x 49 mm | 40 mm x 39,3 mm | _ |
| Power | 3.2 kW -4.3 hp- at 8,250 rpm | 4.6 kW -6.3 hp- at 7,500 rpm | 3.2 kW -4.3 hp- at 6,750 rpm | _ |
| Torque | 3.8 Nm at 7,750 rpm | 6.7 Nm at 5,000 rpm | 4.6 Nm at 6,000 rpm | _ |
| Fuel system | Carburettor | Carburettor | Carburettor | _ |
| Cooling | Forced air | Forced air | Forced air | |
| Lubrication | Wet sump | Wet sump | Mixer controlled according to throttle opening and engine speed | _ |
| Starter | Electric and kick starter | Electric | Electric and kick starter | _ |
| Gearbox | CVT with torque server | CVT with torque server | CVT with torque server | |
| Clutch | Automatic centrifugal dry clutch | Automatic centrifugal dry clutch | Automatic centrifugal dry clutch | |
| Chassis | Single cradle structure in tubular steel with pressed reinforcements | High strength tubular steel single cradle frame | High strength tubular steel single cradle frame | |
| Front suspension | Hydraulic telescopic fork | Hydraulic telescopic fork | Hydraulic telescopic fork | |
| Rear suspension | Hydraulic monoshock absorber | Hydraulic shock absorber | Hydraulic shock absorber | _ |
| Brake front | Hydraulically operated Ø 220 mm disc | Hydraulically operated Ø 200 mm disc | Hydraulically operated Ø 200 mm disc | |
| Brake rear | Ø 140 mm drum | Ø 140 mm drum | Ø 140 mm drum | _ |
| Tyre front | Tubeless 120/70 - 12" | Tubeless 120/70 - 12" | Tubeless 120/70 - 12" | _ |
| Tyre rear | Tubeless 120/70 - 12" | Tubeless 120/70 - 12" | Tubeless 120/70 - 12" | _ |
| Length/ Width/Wheelbase | 1,870 mm / 705 mm / 1,345 mm | 1,880 mm / 735 mm / 1,340 mm | 1,880 mm / 735 mm / 1,340 mm | _ |
| Saddle height | 760 mm | 785 mm | 785 mm | |
| Fuel tank capacity | 7 litres (including 1.5 litre reserve) | 8 litres | 7.5 litres | _ |
| Emissions compliance | EURO 2 | EURO 3 | EURO 2 | |

| | | NRG POWER | ZIP | | TYPHOON | |
|---|----------------------------|--|--|--|---|----|
| | | DD (DT)** | SP 50 2T | 50 4T (50 2T)* | 125 (50 2T)* | |
| - | Engine | Hi-Per 2, 2-stroke single cylinder | Hi-Per 2, 2-stroke single cylinder | Hi-Per 4, 4-stroke 2 valve single cylinder (Hi-Per 2, 2-stroke) | 4-stroke 2 valve single cylinder (Hi-Per 2, 2-stroke) | |
| | Engine capacity | 49.4cc | 49.4cc | 49.9 cc (49.4 cc) | 124 cc (49.4 cc) | |
| - | Bore x Stroke | 40 x 39.3 mm | 40 x 39.3 mm | 39 mm x 41.8 mm (40 mm x 39.3 mm) | 57 mm x 48.6 mm (40 mm x 39.3 mm) | |
| - | Power | 3.3 kW -4.5 hp- at 7,250 rpm (3.3 kW -4.5 hp- at 6,500 rpm) | 3.2 kW -4.3 hp- at 7,250 rpm | 2.6 kW -3.5 hp- at 8,500 rpm (3.3 kW -4.5 hp- at 6,700 rpm) | 6.8 kW -9.3 hp- at 8,500 rpm (3 kW -4.1 hp- at 6,500 rpm) | |
| - | Torque | 4.7 Nm at 6,000 rpm (4.9 Nm at 6,250 rpm) | 4.5 Nm at 6,000 rpm | 3.6 Nm at 6,500 rpm (4.3 Nm at 6,500 rpm) | 8.2 Nm at 7,500 rpm (4.6 Nm at 6,000 rpm) | |
| - | Fuel system | Carburettor | Carburettor | Carburettor | Carburettor | |
| | Cooling | Liquid (air) | Liquid | Forced air | Forced air | |
| - | Lubrication | Mixer controlled according to throt- tle opening and engine speed | Mixer controlled according to throt- tle opening and engine speed | Wet sump (automatic mixer control- led according to throttle opening and engine speed) | Wet sump (automatic mixer control- led according to throttle opening and engine speed) | |
| | Starter | Electric and kick starter | Electric and kick starter | Electric and kick starter | Electric (and kick starter) | |
| | Gearbox | CVT with torque server | CVT with torque server | CVT with torque server | CVT with torque server | |
| | Clutch | Automatic centrifugal dry clutch | Automatic centrifugal dry clutch | Automatic centrifugal dry clutch | Automatic centrifugal dry clutch | 11 |
| | Chassis | High strength tubular steel single cradle frame | High strength tubular steel single cradle frame | High strength tubular steel single cradle frame | Single cradle structure in tubular steel with pressed reinforcements | |
| | Front suspension | Hydraulic upside down telescopic fork | Hydraulic single arm shock absorber | Hydraulic telescopic fork | Hydraulic telescopic fork | |
| | Rear suspension | Hydraulic shock absorber | Hydraulic shock absorber | Hydraulic shock absorber | Hydraulic shock absorber with four- position spring preload adjustment (hydraulic shock absorber) | |
| | Brake front | Hydraulically operated Ø 220 mm disc | Hydraulically operated Ø 200 mm disc | Hydraulically operated Ø 175 mm disc | Hydraulically operated Ø 220 mm disc | |
| - | Brake rear | Hydraulically operated Ø 175 mm disc (Ø 110 mm drum) | Ø 110 mm drum | Ø 110 mm drum | Ø 140 mm drum | |
| - | Tyre front | Tubeless 120/70 - 13" | Tubeless 100/80 - 10" | Tubeless 100/80 - 10" | Tubeless 120/80 - 12" | |
| - | Tyre rear | Tubeless 140/60 - 13" | Tubeless 120/70 - 10" | Tubeless 120/70 - 10" | Tubeless 130/80 - 12" | |
| - | Length/ Width/Wheelbase | 1,790 mm / 750 mm / 1,280 mm | 1,700 mm / 680 mm / 1,205 mm | 1,700 mm / 680 mm / 1,200 mm | 1,940 mm / 720 mm / 1,350 mm | |
| - | Saddle height | 810 mm | Adjustable: 750 mm - 765 mm - 780 mm | Adjustable: 750 mm - 765 mm - 780 mm | 765 mm | |
| - | Fuel tank capacity | 6.7 litres | 7.6 litres | 7.3 litres | 7 litres | |
| - | Emissions compliance | EURO 2 | EURO 2 | EURO 2 | EURO 3 (EURO 2) | |

|--|

Piaggio reminds you to wear and fasten your helmet and to ride carefully at all times. The manufacturer reserves the right to modify technical specifications and visual appearance without prior notice. Only original Piaggio spare parts offer a guarantee of quality and ensure that your vehicle continues to function as intended by the manufacturer.









