

This is a preview - click here to buy the full publication



IEC 62591

Edition 1.0 2010-04

INTERNATIONAL STANDARD



**Industrial communication networks – Wireless communication network and
communication profiles – WirelessHART™**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE **XH**

ICS 25.040.40; 35.100.05

ISBN 978-2-88910-769-8

CONTENTS

| | |
|--|----|
| FOREWORD..... | 18 |
| INTRODUCTION..... | 20 |
| 1 Scope..... | 22 |
| 2 Normative references | 22 |
| 3 Terms, definitions, symbols, abbreviations and conventions | 23 |
| 3.1 Reference model terms and definitions | 23 |
| 3.2 Terms and definitions from ISO/IEC 7498-1 terms | 24 |
| 3.2.1 Terms and definitions from ISO/IEC 9545 | 24 |
| 3.2.2 Terms and definitions from ISO/IEC 8824 | 24 |
| 3.2.3 Terms and definitions from ISO/IEC 8825 | 24 |
| 3.3 Specific terms and definitions | 24 |
| 3.4 Abbreviations..... | 33 |
| 3.5 Conventions | 35 |
| 3.5.1 Conventions used for service..... | 35 |
| 3.5.2 Conventions used for DL-protocol (state machine)..... | 36 |
| 3.5.3 Conventions for Application Layer service | 36 |
| 3.5.4 Conventions for the AL-protocol | 39 |
| 4 Physical layer specification and service definition..... | 44 |
| 4.1 Physical layer service definition..... | 44 |
| 4.1.1 General overview..... | 44 |
| 4.1.2 Physical layer services | 44 |
| 4.2 Physical layer protocol specification | 48 |
| 5 Data-link layer service definition – Type 20 elements | 48 |
| 5.1 Data-link layer services | 48 |
| 5.1.1 Facilities of the data-link layer services | 48 |
| 5.1.2 QoS for message service..... | 49 |
| 5.1.3 Sequence of primitives | 50 |
| 5.1.4 DL-TRANSMIT service | 52 |
| 5.1.5 DL-RECEIVE service | 54 |
| 5.1.6 DL-DISCONNECT service | 55 |
| 5.1.7 DL-PATH-FAILURE service | 55 |
| 5.1.8 DL-ADVERTISE service..... | 55 |
| 5.1.9 DL-NEIGHBOR service..... | 56 |
| 5.1.10 DLM-SET | 56 |
| 5.1.11 DLM-GET | 57 |
| 5.1.12 DLM-ACTION | 58 |
| 5.1.13 DLM-EVENT..... | 59 |
| 5.2 Network layer services..... | 59 |
| 5.2.1 Facilities of the network layer services | 59 |
| 5.2.2 QoS for message service..... | 59 |
| 5.2.3 Sequence of primitives | 60 |
| 5.2.4 NL-TRANSMIT Service..... | 60 |
| 5.2.5 NLM-SET | 61 |
| 5.2.6 NLM-GET | 62 |
| 5.2.7 NLM-ACTION | 63 |
| 5.3 Transport layer services | 64 |

| | | |
|-------|--|-----|
| 5.3.1 | Facilities of the transport layer services..... | 64 |
| 5.3.2 | QoS for message service..... | 64 |
| 5.3.3 | Sequence of primitives | 65 |
| 5.3.4 | TL-DATA-TRANSFER Service..... | 66 |
| 5.3.5 | TL-DATA-EXCHANGE Service | 68 |
| 5.3.6 | TLM-SET | 69 |
| 5.3.7 | TLM-GET | 70 |
| 6 | Data-link layer protocol specification – Type 20 elements..... | 71 |
| 6.1 | Overview | 71 |
| 6.1.1 | Data-link layer operation..... | 71 |
| 6.1.2 | Network layer operation..... | 74 |
| 6.1.3 | Device procedures..... | 76 |
| 6.2 | Logical link control..... | 76 |
| 6.2.1 | General DLPDU structure | 76 |
| 6.2.2 | DLPDU-specific structure, encoding and elements of procedure | 79 |
| 6.2.3 | DLPDU Priority and Flow Control..... | 84 |
| 6.2.4 | Error detection and security..... | 85 |
| 6.3 | Medium Access Control | 86 |
| 6.3.1 | Function | 86 |
| 6.3.2 | Slot timing | 87 |
| 6.3.3 | Communication tables and buffers..... | 89 |
| 6.3.4 | Link scheduling..... | 95 |
| 6.3.5 | MAC operation | 100 |
| 6.4 | DL-management-information..... | 112 |
| 6.4.1 | General | 112 |
| 6.4.2 | DL attributes..... | 112 |
| 6.4.3 | DLM actions | 113 |
| 6.5 | Network layer | 113 |
| 6.5.1 | Two level model of NL | 113 |
| 6.5.2 | NPDU structure | 116 |
| 6.5.3 | Security function..... | 118 |
| 6.5.4 | Network layer tables..... | 123 |
| 6.5.5 | NLE machine | 126 |
| 6.5.6 | NLE elements of procedure | 128 |
| 6.5.7 | NL-management information..... | 131 |
| 6.6 | Transport layer | 133 |
| 6.6.1 | General | 133 |
| 6.6.2 | TPDU structure..... | 133 |
| 6.6.3 | Transport pipe table | 134 |
| 6.6.4 | TLE elements of procedure..... | 134 |
| 6.6.5 | TLE state machines | 137 |
| 6.6.6 | TL-management information | 140 |
| 7 | Application layer service definition – Type 20 elements | 141 |
| 7.1 | Common concepts | 141 |
| 7.2 | Data type ASE | 141 |
| 7.2.1 | Overview | 141 |
| 7.2.2 | Formal definition of data type objects | 143 |
| 7.2.3 | FAL defined data types..... | 145 |
| 7.2.4 | Data type ASE service specification | 148 |

| | | |
|---------|---|-----|
| 7.2.5 | Summary of data types | 148 |
| 7.3 | Communication model specification | 149 |
| 7.3.1 | Common parameters | 149 |
| 7.3.2 | ASEs | 150 |
| 7.3.3 | ARs | 217 |
| 7.3.4 | Summary of classes | 220 |
| 7.3.5 | Permitted services by AREP role | 220 |
| 8 | Application layer protocol specification – Type 20 elements | 221 |
| 8.1 | Abstract syntax | 221 |
| 8.2 | Transfer syntax | 221 |
| 8.2.1 | Common APDU fields | 221 |
| 8.2.2 | Common APDU structure | 222 |
| 8.2.3 | Device application service-specific APDU structures | 225 |
| 8.2.4 | Layer management service specific APDU structures | 249 |
| 8.2.5 | Gateway and network manager specific APDU structures | 291 |
| 8.2.6 | Network management configuration specific APDU structures | 303 |
| 8.2.7 | Data coding rules | 319 |
| 8.3 | Common procedures | 324 |
| 8.3.1 | Delayed response | 324 |
| 8.3.2 | Response time | 327 |
| 8.4 | FAL service protocol machine (FSPM) | 328 |
| 8.4.1 | General | 328 |
| 8.4.2 | FSPM state tables | 328 |
| 8.4.3 | Functions used by FSPM | 330 |
| 8.4.4 | Parameters of FSPM/ARPM primitives | 331 |
| 8.5 | Application relationship protocol machines (ARPMs) | 332 |
| 8.5.1 | AREP mapping to transport layer | 332 |
| 8.5.2 | Application relationship protocol machines (ARPMs) | 333 |
| 8.5.3 | AREP state machine primitive definitions | 335 |
| 8.5.4 | AREP state machine functions | 336 |
| 8.6 | TL mapping protocol machine (TMPM) | 336 |
| 8.6.1 | TMPM states | 336 |
| 8.6.2 | TMPM state machines | 336 |
| 8.6.3 | Primitives exchanged between transport layer and TMPM | 337 |
| 8.6.4 | Functions used by TMPM | 337 |
| 9 | Communication Profile Family 9 (HART™) | 338 |
| 9.1 | General Overview | 338 |
| 9.2 | Profile 9/1 | 338 |
| 9.3 | Profile 9/2 | 338 |
| 9.3.1 | Conformance statement | 338 |
| 9.3.2 | Device types | 339 |
| 9.3.3 | Physical layer | 342 |
| 9.3.4 | Data-link layer | 346 |
| 9.3.5 | Application layer | 347 |
| Annex A | (normative) Security | 355 |
| Annex B | (normative) Wireless procedures | 368 |
| Annex C | (normative) Network management | 372 |
| Annex D | (normative) Gateway | 376 |

| | |
|--|-----|
| Annex E (normative) Command response codes | 381 |
| Annex F (normative) Common tables | 390 |
| Annex G (informative) Application of publish data mode and event commands..... | 404 |
| Annex H (informative) Network redundancy | 408 |
| Annex I (informative) Network manager implementation..... | 409 |
| Annex J (informative) Gateway implementation..... | 433 |
| Annex K (informative) Handheld device | 444 |
| Bibliography..... | 446 |
| | |
| Figure 1 – Superframe class example | 41 |
| Figure 2 – Inheritance example..... | 42 |
| Figure 3 – Basic aggregation example | 43 |
| Figure 4 – Composition aggregation example | 43 |
| Figure 5 – Physical layer service sequences..... | 45 |
| Figure 6 – Message service error-free sequences..... | 51 |
| Figure 7 – Message service sequences with errors | 52 |
| Figure 8 – Receive only message service | 52 |
| Figure 9 – NLL Data transfer service sequences..... | 60 |
| Figure 10 – Data transfer service error-free sequences..... | 65 |
| Figure 11 – Data transfer service sequences with errors..... | 66 |
| Figure 12 – A TDMA slot and superframe | 72 |
| Figure 13 – Channel hopping | 73 |
| Figure 14 – Wireless network..... | 75 |
| Figure 15 – DLPDU Structure | 76 |
| Figure 16 – Address specifier | 76 |
| Figure 17 – Construction of 8-octet EUI-64 Address..... | 78 |
| Figure 18 – DLPDU specifier..... | 78 |
| Figure 19 – Slot timing details..... | 87 |
| Figure 20 – DLE tables and relationship | 90 |
| Figure 21 – Relationships used for link scheduling..... | 97 |
| Figure 22 – MAC components..... | 100 |
| Figure 23 – TDMA state machine | 102 |
| Figure 24 – XMIT state machine | 106 |
| Figure 25 – RECV state machine | 109 |
| Figure 26 – ACK transmission state machine | 111 |
| Figure 27 – Graph routing..... | 114 |
| Figure 28 – Source routing..... | 115 |
| Figure 29 – NPDU Structure | 116 |
| Figure 30 – NPDU control octet | 116 |
| Figure 31 – Security control octet | 118 |
| Figure 32 – NLE tables and relationship | 124 |
| Figure 33 – NLE state machine..... | 127 |
| Figure 34 – Routing decision of the NPDU | 130 |

| | |
|--|-----|
| Figure 35 – TPDU Structure | 133 |
| Figure 36 – TPDU control octet | 133 |
| Figure 37 – Transition diagram of the client data transfer state machine | 138 |
| Figure 38 – Transition diagram of the client data exchange state machine | 138 |
| Figure 39 – Transition diagram of the server state machine | 139 |
| Figure 40 – Data type class hierarchy | 142 |
| Figure 41 – Request APDU format from master to slave | 222 |
| Figure 42 – Normal response APDU format from slave to master | 223 |
| Figure 43 – Command error response APDU format from slave to master | 223 |
| Figure 44 – Aggregated command APDU | 224 |
| Figure 45 – Windowed trigger mode | 236 |
| Figure 46 – Windowed trigger mode with maximum update time expired | 236 |
| Figure 47 – Level trigger mode | 237 |
| Figure 48 – Coding without identification | 319 |
| Figure 49 – Coding of Integer type data | 320 |
| Figure 50 – Coding of Unsigned type data | 320 |
| Figure 51 – Coding of single precision Floating Point type data | 321 |
| Figure 52 – Coding of double precision Floating Point type data | 321 |
| Figure 53 – Coding of Date type data | 322 |
| Figure 54 – Normal DR operation | 325 |
| Figure 55 – Command responses during DR processing | 326 |
| Figure 56 – Slaves with multiple DR buffers | 327 |
| Figure 57 – State transition diagram of FSPM | 328 |
| Figure 58 – State transition diagram of the client ARPM | 334 |
| Figure 59 – State transition diagram of the server ARPM | 335 |
| Figure 60 – State transition diagram of TMPM | 336 |
| Figure 61 – Wireless network components | 340 |
| Figure A.1 – Join sequence | 358 |
| Figure A.2 – Network layer join procedure | 362 |
| Figure A.3 – Data-link layer join procedure | 364 |
| Figure A.4 – Network Key change operation | 366 |
| Figure B.1 – Neighbor Discovery | 369 |
| Figure B.2 – Path failure | 370 |
| Figure B.3 – Device leaving the network | 371 |
| Figure C.1 – Network manager in wireless network | 372 |
| Figure D.1 – Single network access point with clock | 377 |
| Figure D.2 – Multiple network access points with clocks | 377 |
| Figure D.3 – Network access point not providing clock | 378 |
| Figure G.1 – Enabling or disabling publishing sequence | 405 |
| Figure H.1 – Network routing | 408 |
| Figure I.1 – General model for network manager | 410 |
| Figure I.2 – Device type data model | 411 |
| Figure I.3 – Network routing | 412 |

| | |
|---|-----|
| Figure I.4 – Network schedule | 414 |
| Figure I.5 – Example of a three-slot superframe..... | 415 |
| Figure I.6 – Multiple superframes in a network..... | 415 |
| Figure I.7 – Security manager..... | 417 |
| Figure I.8 – Detailed model of the network manager | 418 |
| Figure I.9 – Four network device wireless network | 424 |
| Figure I.10 – APDU sequences | 429 |
| Figure I.11 – Initializing a wireless network..... | 430 |
| Figure I.12 – Allocating and using network resources | 431 |
| Figure I.13 – Adjusting network schedule..... | 432 |
| Figure I.14 – Health reports | 432 |
| Figure J.1 – General model for gateway..... | 434 |
| Figure J.2 – Logical network device | 435 |
| Figure J.3 – Physical network device | 435 |
| Figure J.4 – Managing notification services..... | 440 |
| | |
| Table 1 – Conventions used for state machines | 40 |
| Table 2 – Class relationship notation | 42 |
| Table 3 – Multiplicity notation | 43 |
| Table 4 – PH-ENABLE primitives and parameters | 45 |
| Table 5 – PH-CCA primitives and parameters..... | 46 |
| Table 6 – PH-DATA primitives and parameters..... | 46 |
| Table 7 – PHM-SET primitive and parameters..... | 47 |
| Table 8 – PHM-GET primitive and parameters | 48 |
| Table 9 – DL-Transmit primitives and parameters | 53 |
| Table 10 – DL-RECEIVE primitive and parameters..... | 54 |
| Table 11 – DL-DISCONNECT primitive and parameters..... | 55 |
| Table 12 – DL-PATH-FAILURE primitive and parameters..... | 55 |
| Table 13 – DL-ADVERTISE primitive and parameters | 56 |
| Table 14 – DL-NEIGHBOR primitive and parameters | 56 |
| Table 15 – DLM-SET primitive and parameters..... | 57 |
| Table 16 – DLM-GET primitive and parameters | 57 |
| Table 17 – DLM-ACTION primitive and parameters..... | 58 |
| Table 18 – NL-TRANSMIT primitives and parameters | 60 |
| Table 19 – NLM-SET primitive and parameters..... | 62 |
| Table 20 – NLM-GET primitive and parameters | 62 |
| Table 21 – NLM-ACTION primitive and parameters..... | 63 |
| Table 22 – TL-DATA-TRANSFER primitives and parameters | 66 |
| Table 23 – TL-DATA-EXCHANGE primitives and parameters..... | 68 |
| Table 24 – TLM-Set primitive and parameters..... | 70 |
| Table 25 – TLM-Get primitive and parameters | 70 |
| Table 26 – Network_ID Allocation | 77 |
| Table 27 – Contents of the ACK DLPDU payload | 80 |

| | |
|---|-----|
| Table 28 –ACK response-code | 80 |
| Table 29 – Contents of the Advertise DLPDU payload | 82 |
| Table 30 – Beginning of the superframe..... | 82 |
| Table 31 – The next field after the last superframe size | 82 |
| Table 32 – Repeated for each link | 82 |
| Table 33 – Channel and frequency assignments | 83 |
| Table 34 – Slot timing definitions and values | 88 |
| Table 35 – Minimum DLE Table and buffer space requirement..... | 90 |
| Table 36 – Superframe attributes | 91 |
| Table 37 – Link attributes | 91 |
| Table 38 – Neighbor attributes and variables | 93 |
| Table 39 – Graph attributes | 94 |
| Table 40 – Packet record | 95 |
| Table 41 – Example Backoff_cntr selection sets | 99 |
| Table 42 – TDMA state machine | 103 |
| Table 43 – XMIT state transitions..... | 107 |
| Table 44 – RECV state machine | 110 |
| Table 45 – ACK transmission state machine | 112 |
| Table 46 – DL attributes..... | 112 |
| Table 47 – DL actions | 113 |
| Table 48 – Counter value..... | 118 |
| Table 49 – Session attributes..... | 120 |
| Table 50 – NPDU nonce | 121 |
| Table 51 – Minimum NLE Table space requirement | 124 |
| Table 52 – Route attributes..... | 125 |
| Table 53 – Source route attributes | 125 |
| Table 54 – TimeTable attributes..... | 126 |
| Table 55 – NLE states | 126 |
| Table 56 – NPDU construction..... | 129 |
| Table 57 – Routing actions | 131 |
| Table 58 – NL attributes..... | 132 |
| Table 59 – NL actions | 132 |
| Table 60 – Transport pipe attributes | 134 |
| Table 61 – Transport control encoding for TL-DATA-TRANSFER request | 135 |
| Table 62 – Transport control encoding for TL-DATA-EXCHANGE request..... | 135 |
| Table 63 – Transport control encoding for TL-DATA-EXCHANGE response | 136 |
| Table 64 – Client data transfer state table | 138 |
| Table 65 – Client data exchange state table | 139 |
| Table 66 – Server state table | 140 |
| Table 67 – Data type summary | 149 |
| Table 68 – Response code values | 149 |
| Table 69 – Read service parameters..... | 153 |
| Table 70 – Write service parameters..... | 155 |

| | |
|---|-----|
| Table 71 – Information report service parameters | 156 |
| Table 72 – Action service parameters | 158 |
| Table 73 – AR get attributes service parameters | 218 |
| Table 74 – AR set attributes service parameters | 219 |
| Table 75 – Class summary..... | 220 |
| Table 76 – Confirmed services by AREP class..... | 220 |
| Table 77 – Unconfirmed services by AREP class | 220 |
| Table 78 – Response code values | 221 |
| Table 79 – Extended status values | 222 |
| Table 80 – Reset configuration changed flags value field..... | 226 |
| Table 81 – Reset configuration changed flag command specific Response codes | 226 |
| Table 82 – Perform self test command specific Response codes | 227 |
| Table 83 – Perform device reset command specific Response codes..... | 227 |
| Table 84 – Read additional device status value field..... | 228 |
| Table 85 – Read additional device status command specific Response codes | 228 |
| Table 86 – Read additional device status value field..... | 229 |
| Table 87 – Read additional device status command specific Response codes | 229 |
| Table 88 – Read device variable information value field..... | 230 |
| Table 89 – Read device variable information response value field | 230 |
| Table 90 – Read device variable information command specific Response codes | 231 |
| Table 91 – Write device variable value field..... | 231 |
| Table 92 – Write device variable command specific response codes..... | 232 |
| Table 93 – Read real-time clock value field..... | 233 |
| Table 94 – Read real-time clock command specific response codes | 233 |
| Table 95 – Write publish data period value field..... | 233 |
| Table 96 – Write publish data period command specific response codes..... | 234 |
| Table 97 – Write publish data trigger field..... | 235 |
| Table 98 – Write publish data trigger command specific response codes | 235 |
| Table 99 – Publish data message trigger source..... | 236 |
| Table 100 – Read publish data mode configuration request value field | 237 |
| Table 101 – Read publish data mode configuration response value field..... | 238 |
| Table 102 – Read publish data mode configuration command specific response codes..... | 238 |
| Table 103 – Flush delayed responses command specific Response codes | 239 |
| Table 104 – Write publish data mode configuration value field | 240 |
| Table 105 – Write publish data device variables command specific response codes | 240 |
| Table 106 – Write publish data mode command number value field | 241 |
| Table 107 – Write publish data mode command number value field | 241 |
| Table 108 – Write publish data mode command number command specific response codes..... | 241 |
| Table 109 – Write publish data mode control value field | 242 |
| Table 110 – Write publish data mode control command specific response codes | 242 |
| Table 111 – Read event notification summary request value field | 244 |
| Table 112 – Read event notification summary response value field..... | 244 |

| | |
|---|-----|
| Table 113 – Read event notification summary command specific response codes..... | 244 |
| Table 114 – Write event notification bit mask value field | 245 |
| Table 115 – Write event notification bit mask command specific response codes | 245 |
| Table 116 – Write event notification timing value field..... | 246 |
| Table 117 – Write event notification timing command specific response codes | 246 |
| Table 118 – Write event notification control value field..... | 247 |
| Table 119 – Write event notification control command specific response codes | 247 |
| Table 120 – Write event notification acknowledgement value field | 248 |
| Table 121 – Write event notification acknowledgement command specific response codes..... | 248 |
| Table 122 – Write Join_key value field..... | 249 |
| Table 123 – Write Join_key command specific response codes | 249 |
| Table 124 – Read join status value field..... | 250 |
| Table 125 – Read join status command specific response codes | 250 |
| Table 126 – Write Active_search_shed_time request value field | 250 |
| Table 127 – Write Active_search_shed_time response value field..... | 251 |
| Table 128 – Write Active_search_shed_time command specific response codes | 251 |
| Table 129 – Write Join mode configuration value field | 252 |
| Table 130 – Write Join mode configuration command specific response codes | 252 |
| Table 131 – Read Join mode configuration response value field | 253 |
| Table 132 – Read Join mode configuration command specific response codes | 253 |
| Table 133 – Write network_ID value field..... | 253 |
| Table 134 – Write network_ID command specific response codes..... | 254 |
| Table 135 – Read network_ID value field..... | 254 |
| Table 136 – Read network_ID command specific response codes..... | 254 |
| Table 137 – Write Network_tag value field | 255 |
| Table 138 – Write Network_tag command specific Response codes | 255 |
| Table 139 – Read Network_tag response value field..... | 256 |
| Table 140 – Read Network_tag command-specific response codes | 256 |
| Table 141 – Read wireless device capabilities value field | 256 |
| Table 142 – Read wireless device capabilities command specific response codes | 256 |
| Table 143 – Read battery life response value field | 257 |
| Table 144 – Read battery life command-specific response codes..... | 257 |
| Table 145 – Report device health response value field | 258 |
| Table 146 – Report device health command specific response codes | 258 |
| Table 147 – Read neighbor health list request value field | 258 |
| Table 148 – Read neighbor health list response value field..... | 259 |
| Table 149 – Read neighbor health list command specific response codes..... | 259 |
| Table 150 – Read device nickname response value field | 260 |
| Table 151 – Read device nickname command-specific response codes | 260 |
| Table 152 – Read session list request value field..... | 260 |
| Table 153 – Read session list response value field | 260 |
| Table 154 – Read session list command specific response codes | 261 |

| | |
|---|-----|
| Table 155 – Read superframe list request value field | 261 |
| Table 156 – Read superframe list response value field | 261 |
| Table 157 – Read superframe list command specific response codes | 262 |
| Table 158 – Read link list request value field | 262 |
| Table 159 – Read link list response value field | 262 |
| Table 160 – Read link list command specific response codes | 263 |
| Table 161 – Read graph list request value field | 263 |
| Table 162 – Read graph list response value field | 263 |
| Table 163 – Read graph list command specific response codes | 263 |
| Table 164 – Read neighbor attribute flag request value field | 264 |
| Table 165 – Read neighbor attribute flag response value field | 264 |
| Table 166 – Read neighbor attribute flag command specific response codes | 264 |
| Table 167 – Read neighbor signal level request value field | 265 |
| Table 168 – Read neighbor signal level response value field | 265 |
| Table 169 – Read neighbor signal level command specific response codes | 265 |
| Table 170 – Report path down alarm response value field | 266 |
| Table 171 – Report path down alarm command specific response codes | 266 |
| Table 172 – Report source route failed alarm response value field | 266 |
| Table 173 – Report source route failed alarm command specific response codes | 266 |
| Table 174 – Report graph route failed alarm response value field | 267 |
| Table 175 – Report graph route failed alarm command specific response codes | 267 |
| Table 176 – Report transport layer failed alarm response value field | 267 |
| Table 177 – Report transport layer failed alarm command specific response codes | 267 |
| Table 178 – Write UTC time mapping value field | 268 |
| Table 179 – Write UTC time mapping command specific response codes | 268 |
| Table 180 – Read UTC time mapping response value field | 268 |
| Table 181 – Read UTC time mapping command specific response codes | 269 |
| Table 182 – Write timer interval value field | 269 |
| Table 183 – Write timer interval command specific response codes | 269 |
| Table 184 – Read timer interval request value field | 270 |
| Table 185 – Read timer interval response value field | 270 |
| Table 186 – Read timer interval command specific response codes | 270 |
| Table 187 – Write radio power output value field | 270 |
| Table 188 – Write radio power output command specific response codes | 271 |
| Table 189 – Read radio power output response value field | 271 |
| Table 190 – Read radio power output command specific response codes | 272 |
| Table 191 – Request TimeTable value field | 272 |
| Table 192 – Request TimeTable command specific response codes | 273 |
| Table 193 – Read TimeTable list request value field | 273 |
| Table 194 – Read TimeTable list response value field | 274 |
| Table 195 – Read TimeTable list command specific response codes | 274 |
| Table 196 – Delete TimeTable request value field | 275 |
| Table 197 – Delete TimeTable response value field | 275 |

| | |
|--|-----|
| Table 198 – Delete TimeTable command specific response codes | 275 |
| Table 199 – Read route list request value field | 275 |
| Table 200 – Read route list response value field | 276 |
| Table 201 – Read route list command specific response codes | 276 |
| Table 202 – Read source route request value field | 276 |
| Table 203 – Read source route response value field | 277 |
| Table 204 – Read source route command specific response codes | 277 |
| Table 205 – Read CCA mode response value field | 277 |
| Table 206 – Read CCA mode command specific response codes | 277 |
| Table 207 – Write CCA mode value field | 278 |
| Table 208 – Write CCA mode command specific response codes | 278 |
| Table 209 – Read handheld superframe response value field | 279 |
| Table 210 – Read handheld superframe command specific response codes | 279 |
| Table 211 – Write handheld superframe value field | 279 |
| Table 212 – Write handheld superframe command specific response codes | 279 |
| Table 213 – Read packet hop-to-live response value field | 280 |
| Table 214 – Read packet hop-to-live command specific response codes | 280 |
| Table 215 – Write packet hop-to-live value field | 280 |
| Table 216 – Write packet hop-to-live command specific response codes | 281 |
| Table 217 – Read Join_priority response value field | 281 |
| Table 218 – Read Join_priority command specific response codes | 281 |
| Table 219 – Write Join_priority value field | 282 |
| Table 220 – Write Join_priority command specific response codes | 282 |
| Table 221 – Read receive Priority_threshold response value field | 282 |
| Table 222 – Read receive Priority_threshold command specific response codes | 283 |
| Table 223 – Write receive Priority_threshold value field | 283 |
| Table 224 – Write receive Priority_threshold command specific response codes | 283 |
| Table 225 – Read device list request value field | 284 |
| Table 226 – Read device list response value field | 284 |
| Table 227 – Read device list command specific response codes | 284 |
| Table 228 – Add device list entry request value field | 285 |
| Table 229 – Add device list entry response value field | 285 |
| Table 230 – Add device list entry command specific response codes | 285 |
| Table 231 – Delete device list entry request value field | 286 |
| Table 232 – Delete device list entry response value field | 286 |
| Table 233 – Delete device list entry command specific response codes | 286 |
| Table 234 – Read channel blacklist response value field | 287 |
| Table 235 – Read channel blacklist command specific response codes | 287 |
| Table 236 – Write channel blacklist value field | 287 |
| Table 237 – Write channel blacklist command specific response codes | 288 |
| Table 238 – Read back-off exponent response value field | 288 |
| Table 239 – Read back-off exponent command specific response codes | 288 |
| Table 240 – Write back-off exponent value field | 289 |

| | |
|---|-----|
| Table 241 – Write back-off exponent command specific response codes | 289 |
| Table 242 – Write network access mode value field | 289 |
| Table 243 – Write network access mode command specific response codes | 290 |
| Table 244 – Read network access mode response value field | 290 |
| Table 245 – Read network access mode command specific response codes | 290 |
| Table 246 – Request Session request value field | 291 |
| Table 247 – Request Session response value field | 291 |
| Table 248 – Request Session command specific response codes | 291 |
| Table 249 – Read network device identity request value field | 292 |
| Table 250 – Read network device identity response value field | 292 |
| Table 251 – Read network device identity command specific response codes | 292 |
| Table 252 – Read device’s neighbor health request value field | 292 |
| Table 253 – Read device’s neighbor health response value field | 293 |
| Table 254 – Read device’s neighbor health command specific response codes | 293 |
| Table 255 – Read network topology information request value field | 293 |
| Table 256 – Read network topology information response value field | 294 |
| Table 257 – Read network topology information command specific response codes | 294 |
| Table 258 – Read publish data message list request value field | 294 |
| Table 259 – Read publish data message list response value field | 295 |
| Table 260 – Read publish data message list command specific response codes | 295 |
| Table 261 – Flush cached value field | 295 |
| Table 262 – Flush cached responses command specific response codes | 295 |
| Table 263 – Write update notification bit mask for a device value field | 296 |
| Table 264 – Write update notification bit mask for a device command specific response codes | 296 |
| Table 265 – Read update notification bit mask for a device request value field | 296 |
| Table 266 – Read update notification bit mask for a device response value field | 297 |
| Table 267 – Read update notification bit mask for a device command specific response codes | 297 |
| Table 268 – Report change notification request value field | 297 |
| Table 269 – Report change notification response value field | 297 |
| Table 270 – Report change notification command specific response codes | 298 |
| Table 271 – Read network device statistics request value field | 298 |
| Table 272 – Read network device statistics response value field | 299 |
| Table 273 – Read network device statistics command specific response codes | 299 |
| Table 274 – Read network device identity request value field | 299 |
| Table 275 – Read network device identity response value field | 300 |
| Table 276 – Read network device identity command specific response codes | 300 |
| Table 277 – Write network device's scheduling flags value field | 300 |
| Table 278 – Write network device's scheduling flags command specific response codes | 301 |
| Table 279 – Read network device's scheduling flags request value field | 301 |
| Table 280 – Read network device's scheduling flags response value field | 301 |
| Table 281 – Read network device's scheduling flags command specific response codes | 301 |
| Table 282 – Read network constraints value field | 302 |

| | |
|---|-----|
| Table 283 – Read network constraints command specific response codes | 302 |
| Table 284 – Write network constraints value field | 302 |
| Table 285 – Write network constraints command specific response codes | 303 |
| Table 286 – Disconnect device value field | 303 |
| Table 287 – Disconnect device command specific response codes | 303 |
| Table 288 – Write network key value field | 304 |
| Table 289 – Write network key command specific response codes | 304 |
| Table 290 – Write device nickname value field | 304 |
| Table 291 – Write device nickname command specific response codes | 305 |
| Table 292 – Write session request value field | 305 |
| Table 293 – Write session response value field | 305 |
| Table 294 – Write session command specific response codes | 306 |
| Table 295 – Delete session request value field | 306 |
| Table 296 – Delete session response value field | 306 |
| Table 297 – Delete session command specific response codes | 307 |
| Table 298 – Write superframe request value field | 307 |
| Table 299 – Write superframe response value field | 307 |
| Table 300 – Write superframe command specific response codes | 308 |
| Table 301 – Delete superframe request value field | 308 |
| Table 302 – Delete superframe response value field | 308 |
| Table 303 – Delete superframe command specific response codes | 309 |
| Table 304 – Write link request value field | 309 |
| Table 305 – Write link response value field | 309 |
| Table 306 – Write link command specific response codes | 310 |
| Table 307 – Delete link request value field | 310 |
| Table 308 – Delete link response value field | 311 |
| Table 309 – Delete link command specific response codes | 311 |
| Table 310 – Write graph connection request value field | 311 |
| Table 311 – Write graph connection response value field | 311 |
| Table 312 – Write graph connection command specific response codes | 312 |
| Table 313 – Delete graph connection request value field | 312 |
| Table 314 – Delete graph connection response value field | 312 |
| Table 315 – Delete graph connection command specific response codes | 313 |
| Table 316 – Write neighbor attribute flag value field | 313 |
| Table 317 – Write neighbor attribute command specific response codes | 313 |
| Table 318 – Write network suspend value field | 314 |
| Table 319 – Write network suspend command specific response codes | 314 |
| Table 320 – Write TimeTable request value field | 315 |
| Table 321 – Write TimeTable response value field | 315 |
| Table 322 – Write TimeTable command specific response codes | 315 |
| Table 323 – Write route request value field | 316 |
| Table 324 – Write route response value field | 316 |
| Table 325 – Write route command specific response codes | 316 |

| | |
|---|-----|
| Table 326 – Delete route request value field | 317 |
| Table 327 – Delete route response value field | 317 |
| Table 328 – Delete route command specific response codes | 317 |
| Table 329 – Write source route request value field | 318 |
| Table 330 – Write source route response value field | 318 |
| Table 331 – Write source route command specific response codes | 318 |
| Table 332 – Delete source route request value field | 319 |
| Table 333 – Delete source route response value field | 319 |
| Table 334 – Delete source route command specific response codes | 319 |
| Table 335 – Coding of Integer16 type data | 320 |
| Table 336 – Coding of Unsigned16 type data | 320 |
| Table 337 – Coding for Date type | 322 |
| Table 338 – Coding of 1-octet Bit Field type data | 322 |
| Table 339 – Coding of 2-octet Bit Field type data | 322 |
| Table 340 – Packed ASCII character set | 323 |
| Table 341 – Subset of ISO Latin-1 characters | 324 |
| Table 342 – DRM related response codes | 325 |
| Table 343 – FSPM state Table – client transactions | 328 |
| Table 344 – FSPM state Table – server transactions | 330 |
| Table 345 – Function TransportType () | 330 |
| Table 346 – Function PriorityType () | 330 |
| Table 347 – Function FormReqApdu () | 330 |
| Table 348 – Function FormRspApdu () | 331 |
| Table 349 – Function RetrieveCommand () | 331 |
| Table 350 – Function CommandErr () | 331 |
| Table 351 – Function ResponseCode () | 331 |
| Table 352 – Function DeviceStat () | 331 |
| Table 353 – Function Value () | 331 |
| Table 354 – Parameters used with primitives exchanged between FSPM and ARPM | 332 |
| Table 355 – Client ARPM states | 333 |
| Table 356 – Client ARPM state table | 334 |
| Table 357 – Server ARPM states | 334 |
| Table 358 – Server ARPM state table | 335 |
| Table 359 – Primitives issued from ARPM to TMPM | 335 |
| Table 360 – Primitives issued by TMPM to ARPM | 336 |
| Table 361 – TMPM state descriptions | 336 |
| Table 362 – TMPM state Table – Client transactions | 336 |
| Table 363 – TMPM state Table – Server transactions | 337 |
| Table 364 – Primitives exchanged between network layer and TMPM | 337 |
| Table 365 – CPF 9: overview of profile sets | 338 |
| Table 366 – CP 9/2: PhL protocol selection | 344 |
| Table 367 – Transceiver Specifications | 344 |
| Table 368 – Frequency assignments | 345 |

| | |
|--|-----|
| Table 369 – PHY PIB attributes | 346 |
| Table 370 – CP 9/2: DLL service selection..... | 346 |
| Table 371 – CP 9/2: DLL protocol selection | 347 |
| Table 372 – CP 9/2: AL service selection..... | 347 |
| Table 373 – CP 9/2: Device application service selection..... | 348 |
| Table 374 – CP 9/2: Layer management service selection | 349 |
| Table 375 – CP 9/2: Gateway and network manager service selection | 350 |
| Table 376 – CP 9/2: Network management configuration service selection | 350 |
| Table 377 – CP 9/2: AL protocol selection | 351 |
| Table 378 – Application process status values | 351 |
| Table 379 – CP 9/2: Device application service-specific APDU selection | 352 |
| Table 380 – CP 9/2: Layer management service-specific APDU selection | 353 |
| Table 381 – CP 9/2: Gateway and network manager service-specific APDU selection..... | 354 |
| Table 382 – CP 9/2: Network management configuration service-specific APDU selection | 354 |
| Table C.1 – Network manager requirements | 374 |
| Table D.1 – Cached Response Messages | 380 |
| Table E.1 – Response code values | 381 |
| Table F.1 – Reserved values | 390 |
| Table F.2 – Publish mode control codes | 391 |
| Table F.3 – Write device variable codes | 392 |
| Table F.4 – Device variable family codes | 392 |
| Table F.5 – Device variable classification codes | 393 |
| Table F.6 – Analog channel saturated codes | 394 |
| Table F.7 – Analog channel fixed codes..... | 394 |
| Table F.8 – Standardized status 0 codes | 394 |
| Table F.9 – Standardized status 1 codes | 394 |
| Table F.10 – Standardized status 2 codes | 395 |
| Table F.11 – Standardized status 3 codes | 395 |
| Table F.12 – Publish trigger mode codes | 395 |
| Table F.13 – Event notification control codes..... | 396 |
| Table F.14 – Event status codes..... | 396 |
| Table F.15 – TimeTable request codes | 396 |
| Table F.16 – TimeTable application domain codes..... | 396 |
| Table F.17 – Synchronous action control codes | 397 |
| Table F.18 – Real-time clock flags codes..... | 397 |
| Table F.19 – Wireless timer codes | 397 |
| Table F.20 – Device power source codes..... | 398 |
| Table F.21 – Link_type codes | 398 |
| Table F.22 – Link option flags codes..... | 398 |
| Table F.23 – Superframe mode flags codes | 398 |
| Table F.24 – Session_type codes | 399 |
| Table F.25 – TimeTable deletion reason codes | 399 |

| | |
|---|-----|
| Table F.26 – Disconnect cause codes..... | 399 |
| Table F.27 – Wireless operation codes | 399 |
| Table F.28 – Join process status codes | 400 |
| Table F.29 – Security type codes..... | 400 |
| Table F.30 – Device list codes | 400 |
| Table F.31 – Network access mode codes | 401 |
| Table F.32 – Device profile codes | 401 |
| Table F.33 – Device power status codes..... | 401 |
| Table F.34 – Neighbor flags codes..... | 402 |
| Table F.35 – Notification mask codes | 402 |
| Table F.36 – Join mode codes | 402 |
| Table F.37 – Device scheduling flags codes | 402 |
| Table F.38 – Network optimization flags codes | 403 |
| Table I.1 – Routing requirements | 419 |
| Table I.2 – Scheduling requirements..... | 421 |
| Table I.3 – Frame ID 1: 1 s update rate, superframe length 100..... | 424 |
| Table I.4 – Frame ID 4: 4 s update rate, superframe length 400..... | 424 |
| Table I.5 – Frame ID 0: management superframe | 425 |
| Table I.6 – Join request (shared with management responses)..... | 425 |
| Table I.7 – Join response (shared with management requests)..... | 425 |
| Table I.8 – Commands..... | 425 |
| Table I.9 – Command responses..... | 425 |
| Table I.10 – Device A | 426 |
| Table I.11 – Device B | 427 |
| Table I.12 – Device C | 427 |
| Table I.13 – Device D | 428 |
| Table I.14 – Network manager universal commands | 429 |
| Table J.1 – Required command responses..... | 440 |
| Table J.2 – Gateway status flags | 442 |
| Table J.3 – Gateway capacity guidelines | 443 |

INTERNATIONAL ELECTROTECHNICAL COMMISSION

INDUSTRIAL COMMUNICATION NETWORKS – WIRELESS COMMUNICATION NETWORK AND COMMUNICATION PROFILES – WirelessHART™

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

International Standard IEC 62591 has been prepared by subcommittee 65C: Industrial networks, of IEC technical committee 65: industrial process measurement, control and automation.

This standard cancels and replaces IEC/PAS 62591 published in 2009. This first edition constitutes a technical revision.

The text of this standard is based on the following documents:

| | |
|--------------|------------------|
| FDIS | Report on voting |
| 65C/587/FDIS | 65C/595/RVD |

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

This International standard provides the specification, definitions, and profile for a Wireless communication network. It supplements IEC 61158-5-20, IEC 61158-6-20 where some commands are specified and it supplements IEC 61784-1 where a Communication Profile CP 9/1, universal command, is specified.

This document follows the structure and conventions of IEC 61158 series (for example separation of DL-service definitions and DL-protocol specification) and conventions of IEC 61784-1. IEC 61158 series specify different communication networks. These are structured in different Types. The Type 20 is assigned to technologies of Hart™¹ Communication Foundation (HCF). For other assignments of Type numbers see IEC/TR 61158-1.

NOTE IEC 61158 series do not contain a DLL specification for Type 20. However, this standard includes a DLL specification.

IEC 61784-1, and IEC 61784-2 provide Communication Profile Families (CPF), and, within a family, one to n Communication Profiles. The assigned CPF number for technologies of the HCF is CPF 9. For other assignments of CPF numbers see IEC/TR 61158-1.

A new project number IEC 62591 was assigned to the Type 20 enhancements and the associated CP 9/2, so that this document contains the equivalent subparts of the IEC 61158 series and of IEC 61784-1 organized here in different clauses.

The Type 20 protocol supports two way digital communications for process measurement and control devices. Applications include remote process variable interrogation, cyclical access to process data, parameter setting and diagnostics. This document defines the specification that comprises the Type 20 field communications protocol for wireless devices. Specification of the Type 20 protocol is based largely on the OSI 7-layer Communication Model.

The International Electrotechnical Commission (IEC) draws attention to the fact that it is claimed that compliance with this document may involve the use of patents concerning the claims of the patents listed below given in the normative Clauses.

US08/04750 & PCT 12/100986 [HCF] Combined Wired and Wireless Communications with Field Devices
US08/04777 & PCT 12/100927 [HCF] Increasing Reliability and Reducing Latency in a Wireless Network
US08/04677 & PCT 12/100995 [HCF] Adaptive Scheduling in a Wireless Network
US08/04716 & PCT 12/101000 [HCF] Wireless Protocol Adaptor
US08/04775 & PCT 12/101005 [HCF] Synchronizing Timeslots in a Wireless Communication Protocol
US08/04751 & PCT 12/101011 [HCF] Suspending Transmissions in a Wireless Communication Network
US08/04678 & PCT 12/101021 [HCF] Enhancing Security in a Wireless Network
US08/04746 & PCT 12/101037 [HCF] Wireless Gateway in a Process Control Environment
US08/04676 & PCT 12/101043 [HCF] Efficient Addressing in Wireless HART Protocol
US08/04745 & PCT 12/101049 [HCF] Support for Network Management and Device Communications in a Wireless Network
US08/04749 & PCT 12/101054 [HCF] Priority Based Scheduling and Routing in a Wireless Network
US08/04740 & PCT 12/101071 [HCF] Routing Packets on a Network Using Directed Graphs
US08/04761 & PCT 12/101074 [HCF] Scheduling Communication Frames in a Wireless Network

IEC takes no position concerning the evidence, validity and scope of these patent rights.

¹ HART™ and WirelessHART™ are the trade names of HART™ Communication Foundation (HCF). HCF is a non-profit trade organization to support the HART™ Communication. This information is given for the convenience of users of this International Standard and does not constitute an endorsement by IEC of the trade name holder or any of its products. Compliance to this document does not require use of the trade name. Use of the trade name HART™ and WirelessHART™ requires permission of the trade name holder.

The holder of these patent rights has assured IEC that she/he is willing to negotiate licenses either free of charge or under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of these patent rights is registered with IEC. Information may be obtained from:

[HCF] Hart Communication Foundation
9390 Research Boulevard
Suite I-350
Austin TX 78759, USA

Attention is drawn to the possibility that some of the elements of this standard may be the subject of patent rights other than those identified above. IEC shall not be held responsible for identifying any or all such patent rights.

ISO (www.iso.org/patents) and IEC (http://www.iec.ch/tctools/patent_decl.htm) maintain on-line data bases of patents relevant to their standards. Users are encouraged to consult the data bases for the most up to date information concerning patents.

INDUSTRIAL COMMUNICATION NETWORKS – WIRELESS COMMUNICATION NETWORK AND COMMUNICATION PROFILES – WirelessHART™

1 Scope

This International Standard specifies an additional Type 20 communication network to IEC 61158-5-20, IEC 61158-6-20 and a Communication Profile CP 9/2 in addition to IEC 61784-1 CPF 9.

This standard specifies the following:

- Physical layer service definition and protocol specification,
- Data-link layer service and protocol,
- Application layer service and protocol,
- Network management,
- Security,
- Communication profile,
- Wireless procedures and
- Gateway.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60559, *Binary floating-point arithmetic for microprocessor systems*

IEC/TR 61158-1:2010³, *Industrial communication networks – Fieldbus specifications – Part 1: Overview and guidance for the IEC 61158 and IEC 61784 series*

IEC 61158-5-20:2010², *Industrial communication networks – Fieldbus specifications – Part 5-20: Application layer service definition – Type 20 elements*

IEC 61158-6-20:2010², *Industrial communication networks – Fieldbus specifications – Part 6-20: Application layer protocol specification – Type 20 elements*

IEC 61784-1:2010³, *Industrial Communication Networks – Profiles – Part 1: Fieldbus profiles*

IEC 61784-2:2010³, *Industrial Communication Networks – Profiles – Part 2: Part 2: Additional fieldbus profiles for real-time networks based on ISO/IEC 8802-3*

ISO/IEC 7498-1, *Information technology – Open Systems Interconnection — Basic Reference Model: The Basic Model*

² To be published

ISO/IEC 8824, *Information Technology – Open Systems Interconnection – Specification of Abstract Syntax Notation One (ASN.1)*

ISO/IEC 8859-1, *Information technology – 8-bit single-byte coded graphic character sets – Part 1: Latin alphabet No. 1*

ISO/IEC 9545, *Information technology – Open Systems Interconnection – Application Layer structure*

ISO/IEC 10731, *Information technology – Open Systems Interconnection – Basic Reference Model – Conventions for the definition of OSI services*

IEEE 802-2001, *IEEE Standard for Local and Metropolitan Area Networks: Overview and Architecture*

IEEE 802.15.4-2006, *IEEE Standard for Information technology- Telecommunications and information exchange between systems- Local and metropolitan area networks- Specific requirements Part 15.4: Wireless Medium Access Control (MAC) and Physical Layer (PHY) Specifications for Low-Rate Wireless Personal Area Networks (WPANs)*