

## FEATURES & SPECIFICATIONS

**INTENDED USE** — Ideal for task lighting, restrooms, under/over cabinet, storage closets and displays. **Certain airborne contaminants can diminish integrity of acrylic.** [Click here for Acrylic Environmental Compatibility table for suitable uses.](#)

**CONSTRUCTION** — Lightweight compact-designed channel and cover are formed from cold-rolled steel and painted after fabrication.

Finish: High-gloss, baked white enamel (standard).

**OPTICS** — LEDs provide 88 color rendering index (CRI) at 4000 Kelvin with lumen output of 2,100 lumens. Diffuse acrylic lens providing a single smooth line of light shaped to resemble a fluorescent tube.

**ELECTRICAL** — 80% lumen maintenance at 60,000 hours; predicted life of more than 50,000 hours.

**INSTALLATION** — Snap-lock tool-less channel cover for quick and easy installation. Mounting hardware included for surface mounting on ceiling or wall (horizontally or vertically). Not designed for continuous row mounting or daisy chaining.

**LISTINGS** — UL/C-UL listed to US and Canadian Safety Standards. For use in ambient temperatures from -22°F (-30°C) to 77°F (25°C). Approved FCC Part 15 Class B.

**WARRANTY** — 5-year limited warranty. Complete warranty terms located at [www.acuitybrands.com/CustomerResources/Terms\\_and\\_conditions.aspx](http://www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx)

Actual performance may differ as a result of end-user environment and application.

Actual wattage may differ by +/- 10% when operating between 120-277V +/- 10%.

Note: Specifications subject to change without notice.

|                |
|----------------|
| Catalog Number |
| Notes          |
| Type           |

Contractor Select

# LED Dry Location Striplight



| Specifications   |                |             |         |                   |                         |
|--|----------------|-------------|---------|-------------------|-------------------------|
| All dimensions are shown in inches (centimeters) unless otherwise noted. |                |             |         |                   |                         |
| LUMENS   | LENGTH         | WIDTH       | DEPTH   | WEIGHT            | COMPARABLE LIGHT SOURCE |
| 2100   | 46-1/2 (118.1) | 1-1/2 (3.8) | 2 (5.1) | 3.96 lbs (1.8 kg) | 1 - 32W T8              |

### ORDERING INFORMATION

| Catalog number | UPC           | Description                 | Lumens | Wattage | Voltage   | Color temperature | Pallet quantity | Standard carton quantity |
|----------------|---------------|-----------------------------|--------|---------|-----------|-------------------|-----------------|--------------------------|
| MNSL MV M6     | 7535739545437 | LED dry location striplight | 2100   | 24      | 120 - 277 | 4000K, 88 CRI     | 504             | 1                        |

