

## LORD Fusor® 802HD/804HD/805HD/806HD High Definition Sealer

LORD Fusor® 802HD/804HD/805HD/806HD high definition sealer duplicates the look and function of OEM sealers, including sound deadening material, wheel house coatings and “swirled” seam sealers. Fusor high definition (HD) sealer can be spray applied using Fusor sprayable seam sealer dispensing gun (Stock #312). Fusor HD sealer can be used on bare and primed metal as well as SMC and Fiberglass®.

Fusor HD sealer is available in the following colors:

- White – Fusor 802HD Sealer
- Gray – Fusor 804HD Sealer
- Black – Fusor 805HD Sealer
- Beige – Fusor 806HD Sealer

Note: Fusor HD sealer is not to be used as a beadable seam sealer. Fusor HD sealer should never be applied over asphaltic coatings, typically found as mastic patches applied to vehicle bodies or as a tar-like substance on wheel wells and underbodies, as product failure can occur. Removal of asphaltic coatings or other suspect materials is required before applying Fusor HD sealer.

### Usage

#### **Spray Application**

1. If sealing bare metals, scuff the metal surface with a red scratch pad. Blow off area with dry, filtered compressed air.
2. If sealing primed metals, prime the surface using a two-component primer according to paint manufacturer's instructions. Scuff the primed surface with a red scratch pad. Blow off area with dry, filtered compressed air.
3. Cut cartridge tip and puncture foil seal.
4. Insert cartridge into Fusor sprayable seam sealer dispensing gun (Stock #312). Unscrew and remove tube base; insert cartridge without rotating tube; rescrew base for a tight seal (see Illustration A).
5. Adjust the air pressure and spray pattern of dispensing gun to achieve the desired texture and pattern. The texture and pattern will vary with gun distance from the part. A spray out test panel of Fusor HD sealer is recommended.
6. If needed, paint per manufacturer's recommendations immediately or within 30 days.


For more application information, refer to [www.lord.com/fusor](http://www.lord.com/fusor) for standard operating procedures or access application videos by QR code (on back).

### Technical Data

Skin Time*	20-45 minutes @ 70°F (21°C), 50% RH
Paint Time	immediately or up to 30 days without a scuff
Elongation	200%
Chip Resistance	Passed SAE J400
Corrosion Control	60 cycles SAE J2334

*\*Skin time may vary depending on temperature and humidity. Product cures 1/8 inch every 24 hours. Product thickness will determine full cure time.*

**Illustration A**



# LORD USER INSTRUCTIONS

## LORD Fusor Repair Products Lifetime Guarantee\*

LORD Corporation guarantees to the original purchaser that LORD Fusor® Repair Products (adhesives, primers, seam sealers and foams only), when used in strict accordance with LORD Corporation's application and use instructions, will provide a durable bond for the life of the vehicle. This Guarantee covers actual costs incurred by the installer for labor, replacement parts and materials, and for the reasonable cost of loss of use of the vehicle during the period of replacement. THIS GUARANTEE IS NOT APPLICABLE TO APPLICATION EQUIPMENT, INCLUDING BUT NOT LIMITED TO DISPENSING EQUIPMENT, CARTRIDGE TIPS AND ACCESSORIES.

**THIS EXPRESS WARRANTY IS MADE IN LIEU OF AND EXCLUDES ANY AND ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, BY OPERATION OF LAW OR OTHERWISE, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.**

LORD Corporation shall not be liable under any circumstance for any loss, damage, or expense directly or indirectly arising from the application and use of LORD Fusor Products sold hereunder or from any other cause, and LORD Corporation shall not be liable under any circumstances for consequential or incidental damages.

**LORD CORPORATION'S LIABILITY FOR BREACH OF WARRANTY HEREUNDER IS IN ALL INSTANCES LIMITED SOLELY AND EXCLUSIVELY TO THE REASONABLE COSTS OF REPAIR AND/OR REPLACEMENT OF THE BONDED METAL COMPONENTS OF THE VEHICLE.**

This Lifetime Guarantee shall only apply to the above listed LORD Fusor products sold by LORD Corporation on or after January 1, 2001.

LORD Fusor Metal Bonding Adhesives shall only be used for bonding metal to metal (steel or aluminum) in full or partial panel replacements of:

- door skins
- roof skins
- other outer body sheet metal
- quarter panels
- rear body panels

LORD Fusor products SHALL NOT be used for bonding structural components such as rails, pillars, rocker panels, core supports, etc. If in doubt as to what is a structural component, contact the vehicle manufacturer. If you have any questions or need to receive proper use instructions, contact the LORD Customer Support Center at +1 877 ASK LORD (275 5673) or visit [www.lord.com](http://www.lord.com).

**To comply with the requirements of the LORD Fusor Repair Products Lifetime Guarantee, attach a copy of this completed page to the repair record, and retain with your files:**

**Vehicle Make/Model:** \_\_\_\_\_

**Vehicle Identification Number:** \_\_\_\_\_

**LORD Fusor Product(s) Used for Repair:** \_\_\_\_\_

**Lot Number(s) on Cartridge(s) Used for Repair:** \_\_\_\_\_

*\*This guarantee is void if adhesive is used after the date printed on the cartridge label.*

## Cautionary Information

Before using this or any LORD product, refer to the Safety Data Sheet (SDS) and label for safe use and handling instructions.

*For industrial/commercial use only.* Must be applied by trained personnel only. Not to be used in household applications. Not for consumer use.

*Fiberglass is a trademark of Owens-Corning Fiberglas Corporation.*

Instructions contained in this document need to be followed to qualify for the LORD Fusor Lifetime Guarantee. Values stated in these instructions represent typical values as not all tests are run on each lot of material produced. For formalized product specifications for specific product end uses, contact the Customer Support Center.

Information provided herein is based upon tests believed to be reliable. In as much as LORD Corporation has no control over the manner in which others may use this information, it does not guarantee the results to be obtained. In addition, LORD Corporation does not guarantee the performance of the product or the results obtained from the use of the product or this information where the product has been repackaged by any third party, including but not limited to any product end-user. Nor does the company make any express or implied warranty of merchantability or fitness for a particular purpose concerning the effects or results of such use.

Fusor and "Ask Us How" are trademarks of LORD Corporation or one of its subsidiaries. I-CAR and Industry Training Alliance are registered trademarks of Inter-Industry Conference on Auto Collision Repair. ASE is a registered trademark of the National Institute for Automotive Service Excellence.



LORD provides valuable expertise in adhesives and coatings, vibration and motion control, and magnetically responsive technologies. Our people work in collaboration with our customers to help them increase the value of their products. Innovative and responsive in an ever-changing marketplace, we are focused on providing solutions for our customers worldwide ... Ask Us How.

### LORD Corporation World Headquarters

111 Lord Drive  
Cary, NC 27511-7923  
USA

### Customer Support Center (in United States & Canada)

+1 877 ASK LORD (275 5673)

[www.lord.com](http://www.lord.com)

For a listing of our worldwide locations, visit [LORD.com](http://LORD.com).



Scan with your smartphone.

**LORD**  
Ask Us How™