Director-General of Trade and Industry

(Attn.: Classification Section, Strategic Trade Controls Branch)

16/F, Trade and Industry Tower

3 Concorde Road, Kowloon City, Hong Kong.

Fax No.: (852) 3525 1526

TRADE AND INDUSTRY DEPARTMENT

Classification Questionnaire for Fibrous or Filamentary Materials SC053 (2015/10) (Revised on 2 October 2015)

(This questionnaire should be completed by the <u>manufacturer</u>. Please provide information showing full specification/composition of the product.)

Manufacturer:							
Brand Name :							
Model No. :							
Part II – General Information							
What is the type of	f	(a) Organic	П				
fibrous or filamentary material for the product		(b) Carbon					
in Part I? (Please put √		(c) Inorganic	\Box				
in the appropriate box.)		(d) Others : please specify					
Part III Technical Information (Specification/Composition for the product in Part I) Please select the appropriate section to answer and put $\sqrt{\ }$ in the appropriate boxes.							
Section (a)	(For Or	ganic fibrous or filamentary materials)	Yes	/ No			
1C010(a)		Having a specific modulus exceeding 12.7 x 10 ⁶ m. Please provide the exact figure in m:)					
	` /	Having a specific tensile strength exceeding 23.5 x 10 ⁴ m. Please provide the exact figure in m:)					
	(Note)	The material is polyethylene.					
Section (b)	(For Ca	rbon fibrous or filamentary materials)	Yes	/ No			
1C010(b)		Having a specific modulus exceeding 14.65 x 10 ⁶ m. Please provide the exact figure in m:)					
		Having a specific tensile strength exceeding 26.82 x 10 ⁴ m. Please provide the exact figure in m:)					
	(Note1) The product is for the repair of civil aircraft structures or laminates, having all of the following:					
	(Note2	 (a) an area not exceeding 1 m²; (b) a length not exceeding 2.5 m; and (c) a width exceeding 15 mm.) Mechanically chopped, milled or cut carbon fibrous or filamentary materials 25.0 mm or less in length.					

Yes / No (For Inorganic fibrous or filamentary materials) Section (c) 1C010(c) Having a specific modulus exceeding 2.54 x 10⁶ m. П П (Please provide the exact figure in m: Having a melting, softening, decomposition or sublimation (2) point exceeding 1922 K (1 649⁰C) in an inert environment. (Note 1) The materials are discontinuous, multiphase, polycrystalline П alumina fibres in chopped fibre or random mat form, containing 3 % by weight or more silica, with a specific modulus of less than 10 x 10⁶ m. П (Note 2) The materials are molybdenum and molybdenum alloy fibres. (Note 3) The materials are boron fibres. (Note 4) The materials are discontinuous ceramic fibres with a melting, softening, decomposition or sublimation point lower than 2043 K (1770⁰C) in an inert environment. Yes / No Section (d) (For other fibrous or filamentary materials) 1C010(d) Being composed of any of the following: **(1)** Bismaleimides; (2) Aromatic polyamide-imides; (3) Aromatic polyimides; **(4)** Aromatic polyetherimides; П (5) Thermoplastic liquid crystal copolymers; (6) Polyarylene ketones; П **(7)** Polyarylene sulphides;

П

(8)

Polybiphenylenethersulphone.

Polymeric Substances'.

If yes for any of (1) to (8) above, please also complete 'SC052-Classification Questionnaire for Non-fluorinated

fibrous or filamentary materials (prepregs), metal or carbon-coated fibrous or filamentary materials (preforms) or Yes / No carbon fibre preforms) 1C010(e) (1)(a) Made from inorganic fibrous or filamentary materials П (If yes, please also complete Section (c) above.) (b) Made from organic or carbon fibrous or filamentary materials with all of the following characteristics: П (i) With specific modulus exceeding 10.15 x 10⁶ m. (Please provide the exact figure in m: П (ii) With specific tensile strength exceeding 17.7 x 10⁴ m. (Please provide the exact figure in m: .) П (2) (a) (i) Resin or pitch specified in Section (d) above. П (If yes for any of (1) to (8) in Section (d) above, please П also complete 'SC052-Classification Questionnaire for Non-fluorinated Polymeric Substances'.) (ii) Resin or pitch having fluorinated polyimides containing П П 10% by weight or more of combined fluorine; (b) Dynamic Mechanical Analysis glass transition temperature (DMA Tg) equal to or exceeding 453 K (180°C) and having a phenolic resin; (Please provide the exact temperature in °C: (c) Dynamic Mechanical Analysis glass transition temperature (DMA Tg) equal to or exceeding 505 K (232°C) and having a resin or pitch, not specified in paragraphs (2)(a)(i) & (ii) of Section (e), and not being a phenolic resin; (Please provide the exact temperature in °C: (Note 1) The product is epoxy resin matrix impregnated carbon П П fibrous or filamentary materials (prepregs) for the repair of civil aircraft structures or laminates, having all of the following: (a)an area not exceeding 1 m²; (b) a length not exceeding 2.5 m; and (c) a width exceeding 15 mm. (Note 2) Fully or partially resin-impregnated or pitch-impregnated mechanically chopped, milled or cut carbon fibrous or filamentary materials 25.0 mm or less in length when using a resin or pitch other than those specified in

paragraphs (2)(a)(i) & (ii) of Section (e).

Section (e)

Section (f)	(For other fibrous or filamentary materials or prepregs)	Yes /	No
Section (f) (i): 1C210 Note	The fibrous or filamentary materials are in the form of continuous monofilaments, yarns, rovings, tows or tapes. (If YES , please complete Section (f) (ii), (iii) or (iv) as appropriate.)		
Section (f) (ii):	Carbon or aramid fibrous or filamentary materials:		
1C210(a)	(1) Having a specific modulus of 12.7 x 10 ⁶ m or greater; or (Please provide the exact figure in m:)		
	(2) Having a specific tensile strength of 235 x 10 ³ m or greater. (Please provide the exact figure in m:)		
	(Note) Whether the materials are aramid fibrous or filamentary materials having 0.25 percent or more by weight of an ester based fibre surface modifier ?		
Section (f) (iii):	Glass fibrous or filamentary materials:		
1C210(b)	(1) Having a specific modulus of 3.18 x 10 ⁶ m or greater; and (Please provide the exact figure in m:)		
	(2) Having a specific tensile strength of 76.2 x 10 ³ m or greater. (Please provide the exact figure in m:)		
Section (f) (iv): 1C210(c)	Thermoset resin impregnated continuous yarns, rovings, tows or tapes with a width of 15 mm or less (prepregs), made from carbon or glass fibrous or filamentary materials specified in Section (f) (ii) or (iii) above. (If YES, please also complete Section (f) (ii) or (iii) as appropriate.)		
	ation (by the Manufacturer of the Product in Part I) st of my knowledge and belief the information given above is true and correct.		
Name of Signator	v. ·		
Name of Signatory : (in block letters)			
Name of Compan			
Position of Signat Company :	ory in the		
Signature & Comp	pany Chop :		
Date:			
Important Note:	The data collected in this form will be kept in confidence. They may however be disclosed to departments, or to third parties in Hong Kong or elsewhere, if such disclosure is necessary to facilitat the related application, is in the interests of the trade in Hong Kong, is authorised or required by the consent to such disclosure is given by the applicant/data subject.	te conside	eration of
	For further information concerning the handling of personal data by the Department, please refer issued by the Department on the subject, copy of which is obtainable from the Strategic Trade Control Trade and Industry Tower, 3 Concorde Road, Kowloon City, Hong Kong.		