

SHERWIN-WILLIAMS CO -- C-775 LATEX CAULK, WHITE -- 8030-00N060791

===== Product Identification =====

Product ID:C-775 LATEX CAULK, WHITE

MSDS Date:11/01/1995

FSC:8030

NIIN:00N060791

MSDS Number: CGZTB

=== Responsible Party ===

Company Name:SHERWIN-WILLIAMS CO

Address:101 PROSPECT AVE

City:CLEVELAND

State:OH

ZIP:44115

Country:US

Info Phone Num:216-566-2902

Emergency Phone Num:216-566-2917

CAGE:54636

=== Contractor Identification ===

Company Name:SHERWIN-WILLIAMS CO THE

Address:101 PROSPECT AVE NW

Box:City:CLEVELAND

State:OH

ZIP:44115-1042

Country:US

Phone:800-251-2486/216-566-2242

CAGE:54636

===== Composition/Information on Ingredients =====

Ingred Name:SOLVENT NAPHTHA, PETROLEUM, MEDIUM ALIPH. VP: 2.0

CAS:64742-88-7

Fraction by Wt: 2%

OSHA PEL:100 PPM (MFR)

ACGIH TLV:100 PPM (MFR)

Ingred Name:ETHYLENE GLYCOL (SARA 313) (CERCLA). VP: 0.1

CAS:107-21-1

RTECS #:KW2975000

Fraction by Wt: 1%

OSHA PEL:C 50 PPM (MFR)

ACGIH TLV:C 50 PPM,VAPOR; 9495

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:CARBONIC ACID, CALCIUM SALT (1:1); (CALCIUM CARBONATE)

CAS:471-34-1

RTECS #:FF9335000

Fraction by Wt: 67%

OSHA PEL:15 MG/M3 (MFR)

ACGIH TLV:10 MG/M3 (MFR)

Ingred Name:SUPDAT: FILM, WEAR A DUST/MIST RESPIRATOR APPROVED BY
NIOSH

FOR PROT AGAINST NON-VOLATILE MATERIALS IN SECTION 2.

RTECS #:9999999ZZ

Ingred Name:EFTS OF OVEREXP: PROLONGED OVEREXPOSURE TO MINERAL SPIRITS
OR V M & P KAPTHA MAY CAUSE ADVERSE EFFECTS TO THE (ING 6)

RTECS #:9999999ZZ

Ingred Name:ING 5: LIVER AND URINARY SYSTEMS.

RTECS #:9999999ZZ

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: IRRITATION OF EYES, SKIN AND
RESPIRATORY SYSTEM. IN A CONFINED AREA VAPORS IN HIGH
CONCENTRATION

MAY CAUSE HEADACHE, NAUSEA OR DIZZINESS. SIGNS AND SYMPTOMS OF
OVEREXPOSURE: REDNESS AND ITCHING OR BURNING SENSATION MAY
INDICATE EYE OR EXCESSIVE SKIN EXPOSURE. CHRONIC: ETHYLENE GLYCOL
IS (EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:HLTH HAZ: CONSIDERED AN ANIMAL TERATOGEN. IT
HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN RATS & MICE AT HIGH DOSES
WHEN GIVEN IN DRINKING WATER/BY SAVAGE. THERE IS NO EVIDENCE TO
INDICATE IT CAUSES BIRTH DEFECTS IN HUMANS. PROLONGED
OVEREXPOSURE

TO ETHYLENE GLYCOL MAY CAUSE ADVERSE EFFECTS TO THE REPRODUCTIVE
SYS. (ING 5)

Medical Cond Aggravated by Exposure:NONE GENERALLY RECOGNIZED.

===== First Aid Measures =====

First Aid:INHAL: REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM AND

QUIET. SKIN: WASH AFFECTED AREA THOROUGHLY WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND LAUNDRER BEFORE RE-USE. EYES: FLUSH

EYES WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. INGEST: SEEK MEDICAL ATTENTION IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:>200F,>93C

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:USE NIOSH APPRVD SCBA & FULL PROT EQUIP . WATER SPRAY MAY BE INEFT. IF H*2O IS USED, FOG NOZZLES ARE PREF. H*2O MAY BE USED TO COOL CLSD CNTNRS (SUPDAT)

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE (DUE TO THE BUILD-UP OF PRESSURE) WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AND REMOVE WITH INERT ABSORBENT. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE.

TRANSFER ONLY TO APPROVED CONTAINERS WITH COMPLETE AND APPROPRIATE LABELING. DO NOT TAKE INTERNALLY.

Other Precautions:KEEP OUT OF THE REACH OF CHILDREN. CA PROPOSITION 65:

WARNING: THESE PRODUCTS, EXCEPT FOR C-99, CONTAIN A CHEMICAL(S) KNOWN TO THE STATE OF CA TO CAUSE CANCER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF PERS EXPOS CANNOT BE CONTROLLED BELOW APPLIC LIMS BY VENT, WEAR A PROPERLY FITTED ORG VAP/PARTICULATE RESP

APPRVD BY NIOSH FOR PROT AGAINST MATLS IN SECTION 2. WHEN
SANDING/ABRADING DRIED FILM, WEA R A DUST/MIST RESP APPRVD
(SUPDAT)

Ventilation:LOC EXHST PREF. GEN EXHST ACCEPTABLE IF THE EXPOS TO MATLS
IN SECTION 2 IS MAINTAINED BELOW APPLIC EXPOS LIMS. (SUPDAT)

Protective Gloves:CHEMICAL RESISTANT GLOVES.

Eye Protection:ANSI APPROVED CHEM WORKERS GOGGS .

Other Protective Equipment:EYE WASH FOUNTAIN & DELUGE SHOWER WHICH
MEET

ANSI DESIGN CRITERIA .

Work Hygienic Practices:WASH HANDS AFTER USING.

Supplemental Safety and Health

FIRE FIGHT PROC:TO PVNT PRESS BUILD-UP & POSS AUTOIGNITION/EXPLOSION
WHEN EXPOSED TO EXTREME HEAT. VENT:REFER TO OSHA STDS 1910.94,
1910.107, 1910.108. RESP PROT:BY NIOSH FOR PROT AGAINST MATLS IN
SEC TION II. WHEN SANDING/ABRADING THE DRIED (ING 4)

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>212F,>100C

Vapor Pres:SEE INGRED

Vapor Density:HVR/AIR

Spec Gravity:1.61

Evaporation Rate & Reference:SLOWER THAN ETHER

Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE KNOWN.

Stability Condition to Avoid:NONE KNOWN.

Hazardous Decomposition Products:BY FIRE: CARBON DIOXIDE, CARBON
MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:WASTE FROM THESE PRODUCT IS NOT HAZARDOUS AS
DEFINED UNDER THE RCRA 40 CFR 261. DISPOSE OF IN ACCORDANCE WITH
FEDERAL, STATE, AND LOCAL REGULATIONS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling
agencies):

This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.