Material Safety Data Sheet May be used to comply with OSHA's Hazard Communication Standard. 29 CFR 1910.1200. Standard must be		U.S. Depar Occupational S (Non-Mandato Form Approve		O r Administration			
consulted for specific requirements.		OMB No. 1218		-			
IDENTITY (As Used on Label and List) Fiehing's Resolene, Neutral, Black	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that						
Section I		· · · · · · · · · · · · · · · · · · ·			······································		
Manulacturer's Name	•	Emergency Telep	hone Number		·		
Flebing Company, Inc.		800-424-	9300				
Address (Number, Sireel, City, State, and ZIP Code) 516 South 2nd Street		(414) 271-	er for Information -5011	79	-		
Milwaukee, WI 53204-0125	Date Prepared	Dale Prepared February, 2002					
	Signature of Preparer (optional)						
Section II - Hazardous Ingredients/Identity	Informatio	n					
Hazardous Components (Specific Chemical Identity; Com	mon Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommenced	% (optional)		
Isopropanol (CAS No. 67-63-0)		400 ppm	400 ppm	N/A			
				· · · ·	•		
					•		
			n general generation and	1			
		····	•	• • • · · · · ·			
Section III — Physical/Chemical Characteris	stics						
Boiling Point Approx.	212 ⁰ F	Specific Gravity ((H ₂ O = 1)	Approx.	1.03		
Vapor Pressure (mm Hg.)		Melting Point					
Vapor Density (AIR + 1)	N.D.	Evaporation Rate	-		N.D.		
Vable Density (Air = 1)	N.D.	(Butyl Acetate =	-	· · ·	N.D.		
Solubility in Water Dilutable	**************************************		-		• <u>••••••</u> •••••••••••••••••••••••••••••		
Appearance and Odor Variously colored liquids, mild a	ammoniaca	l odor.					
Section IV - Fire and Explosion Hazard D	ata		· · · · · · · · · · · · · · · · · · ·				
Flash Point (Method Used)		Flammable Limit	IS	LEL	UEL		
N/A (non-flammable) Exinguishing Media Non-combustable, use foam, carbon	- dt oxt de	dray chemic			N/A		
Special Fire Fighting Procedures	· · · · · · · · · · · · · · · · · · ·						
Not a fire or explosion hazard.	If mater	ial is invol	ved in fire,	wear NIOSH a	pproved		
self-contained breathing apparate	us. Use	water spray	to cool fire	exposed cont	ainers.		
Unusual Fire and Explosion Hazards Material can spatter above 212°F	. Polyme	r film can b	urn.				

(Reproduce locally) N.E.=Not Established, N.D.=Not Determined, N/A=Not Applicable OSHA 174, Sept. 1985

.F:	iebi	.ag.	s Basa	lene,	Neutra.	L	Black	and	Brown
-----	------	------	--------	-------	---------	---	-------	-----	-------

Section V	Reactivity Dat				
	Unstable		Conditions to Avoid		ť,
	Sladie	X	Keep from fre	eezing.	4
lone expect	Matenals to Avoid ted.	_			
azardous Deco	mposition or Byproc carbon.	JUCIS			
azardous olymenzation	May Occur		Conditions to Avoid		
,	Will Not Occur	X	None known.	• • • • • • • • • • • • • • • • • • •	
ection VI -	- Health Hazar		• · · · · · · · · · · · · · · · · · · ·		
loure(s) of Entry	: Ini	nalation?	Yes	Skin? Yes	Ingestion? Yes
Tealin Hazards	Acule and Chronic)	spra	v mist can cau	se headache, nau	sea and irritation of respiratory
					r prolonged contact. Eye contact
cirect pro	duct contac	t may	be irritating	to eyes.	
	N	re' No		IARC Monographs? N	OSHA Regulated? NO
	· • •				
	noms of Exposure	<u>above</u> .			-
Medical Condilio	ns valed by Exposure	No	one known.	·····	
Terrerant vdd.n					
areas wit vomiting.	h soap and Seek medi	water cal a	. Ingestion1		cal aid. Skin contactwash affec two glasses of water, induce
Sleps to Be Tak Floor may	en in Case Maieria be slipper	al is Reie y, us	ased or Spilled e care to avoid	d falling. Dike	and contain spill. Absorb with
	te inert ma				
Waste Oisposal		dance	with federal	state coupty or	nd local regulations.
DISPOSE	of in accor	Jance	with rederar,	state, county at	
Precautions to Keep out	Be Taken in Handli of reach of	ng and S chil	Jonng dren. Keep co	ntainer closed.	Keep from freezing. Avoid contact
	s, skin and				roughly after handing.
Ciner Precaulic	athing vapo		d mists		
				·····	······································
	- Control Me		-		
					n is maintained; otherwise, wear
Venulation	Local Exhaust	-conta	ained breathing	z apparatus. Special	
	Preferred			None	
	Mechanical (Ger Adequate	neral)		Olber None	
Protective Glov	•			Eye Protection	
Impervio Ciner Protectiv	e Clothing or Equi	omeni			plash safety goggles.
Impervio	us clothing	, eye	wash station, e	emergency shower.	
WorwHygienk Handle W	Practices ith due car	e. W	ash thoroughly	after handling.	.
				Page 7	

USGPO 1966-491-529/45775