



**Chemical Name:** Isopropyl Alcohol 91%

**Manufacturer:** HUMCO

**Container size:** 16oz.

**Location:** VLA

**Disposal:** Place empty container in trash. Give partial or full container to the safety officer.

Material Safety Data Sheet

May be used to comply with  
OSHA's Hazard Communication Standard,  
29 CFR 1910.1200. Standard must be  
consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration  
(Non-Mandatory Form)  
Form Approved  
OMB No. 1218-0072

IDENTITY (As Used on Label and List)  <b>ISOPROPYL ALCOHOL</b> <b>91%</b>	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
--	---

Section I

Manufacturer's Name <b>HYDROX LABORATORIES</b>	Emergency Telephone Number <b>800-255-3924</b>
Address (Number, Street, City, State, and ZIP Code) <b>825-B TOLLGATE ROAD</b> <b>ELGIN, IL 60123</b>	Telephone Number for Information <b>847-468-9400</b>
	Date Revised / Reviewed 12/09/08
	Signature of Preparer (optional)

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(optional)
<b>ISOPROPYL ALCOHOL</b> <b>(CAS #67-63-0)</b>  <b>ACUTE HEALTH HAZARD: 2</b> <b>FIRE HAZARD: 3</b> <b>REACTIVITY: 0</b>	<b>PEL/TWA</b> <b>8 Hr. 400 ppm (OSHA/ACGIH)</b> <b>STEL 500 ppm (OSHA/ACGIH)</b> <b>REL TWA 10 Hr. 400 ppm (NIOSH)</b> <b>15 min. ceiling 800 ppm (NIOSH)</b>			

Section III - Physical/Chemical Characteristics

Boiling Point	N/A	Specific Gravity (H <sub>2</sub> O = 1)	0.790 @ 20°C/20°C
---------------	-----	---	-------------------

Approx.			
Vapor Pressure (mm Hg.) Approx.	N/A	Freezing Point Approx.	-32 to -50°C
Vapor Density (AIR = 1) Approx.	N/A	Evaporation Rate (Butyl Acetate = 1) Approx.	1.7
Solubility in Water	COMPLETE.		
Appearance and Odor	COLORLESS LIQUID, CHARACTERISTIC ODOR.		

## Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) <b>Approx. 57° F - TCC</b>	Flammable Limits @ 77°F	LEL <b>2.0</b>	UEL <b>12.0</b>
Extinguishing Media <b>CARBON DIOXIDE, DRY CHEMICAL OR ALCOHOL FOAM FOG.</b>			
Special Fire Fighting Procedures <b>DILUTION OF BURNING LIQUID WITH WATER WILL AFFECT EXTINGUISHMENT.</b>			
Unusual Fire and Explosion Hazards <b>NONE.</b>			

## Section V - Reactivity Data

Stability	Unstable		Conditions to Avoid <b>AVOID HEAT, SPARKS AND OPEN FLAME.</b>
	Stable	X	
Incompatibility ( <i>Materials to Avoid</i> ) <b>ANHYDRIDE, ISOCYANATE, MONOMER AND ORGANO-METALLIC.</b>			
Hazardous Decomposition or Byproducts <b>BURNING MAY PRODUCE CARBON MONOXIDE AND CARBON DIOXIDE CONTAMINATION.</b>			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

## Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation? <b>YES</b>	Skin? <b>NEGLIGIBLE</b>	Ingestion? <b>YES</b>	Eyes? <b>YES</b>
Health Hazards ( <i>Acute and Chronic</i> ) <b>GENERALLY USED AS A RUBDOWN. VAPOR IRRITATES EYES. HIGH CONCENTRATION OF VAPOR CAN IRRITATE RESPIRATORY TRACT, IS ANESTHETIC AND MAY CAUSE CNS</b>				

**DEPRESSION.**

Carcinogenicity:  
**NOT A  
CARCINOGEN**

NTP?

IARC Monographs?

OSHA Regulated?  
Y

Signs and Symptoms of Exposure

**GIDDINESS, HEADACHE, DIZZINESS AND NAUSEA.**

Medical Conditions Generally Aggravated by Exposure

**PRE-EXISTING AND RESPIRATORY DISORDERS, MAY BE AGGRAVATED BY EXPOSURE.**

Emergency and First Aid Procedures

**MOVE TO FRESH AIR. IF SWALLOWED, DO NOT INDUCE VOMITING AND CALL PHYSICIAN. FLUSH SKIN WITH WATER. FLUSH EYES WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS, SEE A PHYSICIAN IMMEDIATELY**

## Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled.

**ELIMINATE ALL SOURCES OF IGNITION. SMALL SPILLS SHOULD BE FLUSHED WITH LARGE QUANTITIES OF WATER. LARGER SPILLS SHOULD BE COLLECTED FOR DISPOSAL.**

Waste Disposal Method

**ATOMIZE INTO AN INCINERATOR WHERE PERMITTED UNDER APPROPRIATE FEDERAL, STATE, AND LOCAL REGULATIONS.**

Precautions to Be taken in Handling and Storing

**DO NOT TAKE INTERNALLY. FLAMMABLE LIQUID. KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAMES. KEEP CONTAINER CLOSED.**

Other Precautions

N/A

## Section VIII - Control Measures

Respiratory Protection (*Specify Type*)

**AIR SUPPLIED MASKS IN CONFINED AREAS.**

Ventilation

Local Exhaust

**PREFERRED**

Special

Mechanical (*General*)

**ACCEPTABLE**

Other

Protective Gloves

**RUBBER OR VINYL GLOVES**

Eye Protection

**CHEMICAL RESISTANT GOGGLES**

Other Protective Clothing or Equipment

**EYE BATH AND SAFETY SHOWERS.**

Work/Hygienic Practices

**HANDLE CAREFULLY; AVOID SPILLING. WASH HANDS BEFORE EATING, DRINKING OR SMOKING.**

**Disclaimer:**

The contents of this MSDS are believed to be correct but do not purport to be all-inclusive and should only be used as a guide. Hydrox Laboratories, Inc. disclaims any express or implied warranty as to the accuracy of the above information and shall not be held liable for any direct, incidental or consequential damages resulting from the reliance on the above information.