

# NW2000T-LED

## 4" 2000 Series - Evolution LED

### IC Air Tight New Construction Housing for GU10 LED Lamp

#### SPECIFICATIONS


HOUSING DETAILS	<p>18 gauge 0.051" (1.3 mm) thickness galvanized steel.</p> <p>Approved for installation in insulated ceiling in direct contact with insulating material (except polyurethane).</p> <p>Air Tight.</p> <p>Junction box can support up to 10 – 14 gauge wires or 8 – 12 gauge wires.</p> <p>Below-ceiling accessible.</p>
-----------------	---

MOUNTING	<p><b>Cutout diameter: Ø 4-1/4" (108 mm)</b></p> <p>Can fit in ceilings up to 1-1/2" (38 mm) thick.</p> <p>Requires a 4-1/2" (114 mm) clearance beyond the ceiling level.</p> <p>Contrast hooks for ease of installation and a perfect fit to ceiling.</p> <p>Mounting bars extend from 10" (254 mm) to 24-1/2" (622 mm) to fit in most ceiling structures (compatible with suspended ceilings).</p> <p>No light leakage.</p>
----------	---

LAMP	<p><b>GU10 LED 9.8W MAX</b></p> <p>This product was designed for GU10 LED lamp. If you want to use a dimmer, please refer regularly to the lamp manufacturer dimmer compatibility list.</p>
------	---

VOLTAGE	120 Volts			
COMPATIBLE TRIMS	R2000 R2000DG R2000V SM	R2051 R2100 R2100VT	R2450VT S2000 S2100	T2000
THERMAL PROTECTION	TC 194°F (90°C)			
CERTIFICATION	<ul style="list-style-type: none"><li>• cULus <b>E343977</b> for damp locations</li><li>• Certified Air Tight ASTM E283</li></ul>			

#### CODIFICATION EXAMPLE



#### ORDERING CODE

MODEL	SERIES	SOURCE
<b>NW</b>	<b>2000</b>	<b>T-LED</b>
<b>NW</b> New Construction	<b>2000</b> 4" Series	<b>T-LED</b> GU10 LED Lamp

Project	
Notes	
Fixture Type	
Date	

